

Article

Evaluating Indirect Prompt Injection Defenses in Tool-Using LLM Agents: Security, Utility, and Replication

Adil Khan ¹, Khaled AlKhanbashi ¹ and Azza Mohamed ^{2,*}

¹ General Education Department, Liwa University, Abu Dhabi P.O. Box 41009, United Arab Emirates; adil.khan@lu.ac.ae (A.K.); khaled.alkhanbashi@lu.ac.ae (K.A.)

² Electrical and Computer Engineering Department, College of Engineering, Abu Dhabi University, Abu Dhabi P.O. Box 59911, United Arab Emirates

* Correspondence: azza.basiouni@adu.ac.ae

Abstract

Large language model (LLM) agents that retrieve external content and use tools are vulnerable to indirect prompt injection, in which untrusted content contains instructions intended to influence agent behavior. We evaluated four defenses and an undefended control across GPT-5.4, GPT-5.4-mini, and Claude Sonnet 4.6 on the AgentDojo banking benchmark (Tool Filter was evaluated only for the OpenAI models), reporting attack success rate (ASR), benign utility, utility under attack, operational measures, and two independent benchmark replications. Raw undefended ASR was 0/288 for GPT-5.4, 11/288 for GPT-5.4-mini, and 1/288 for Claude Sonnet 4.6; these cross-model differences require cautious interpretation because benchmark goals were not equally reachable across models. For GPT-5.4-mini, the Prompt Injection Detector and Tool Filter were associated with lower observed ASRs but also lower benign utility, and Tool Filter restricted available actions. None of the four paired GPT-5.4-mini comparisons reached significance after Holm correction; only Tool Filter had an unadjusted *p*-value below 0.05. Benign utility was more stable across runs than individual low-frequency attack outcomes. The findings show that defense evaluation should report attack outcomes, goal feasibility, legitimate-task utility, action availability, operational measures, and run-to-run variation. Results are limited to the evaluated benchmark, models, defenses, and conditions.

Keywords: indirect prompt injection; LLM agents; tool use; AgentDojo; defense evaluation; security–utility trade-off; LLM security



Academic Editors: Leandros Maglaras, Helge Janicke, Alexios Lekidis and Mohamed Amine Ferrag

Received: 21 July 2026

Revised: 21 August 2026

Accepted: 28 August 2026

Published: 31 August 2026

Copyright: © 2026 by the authors.

Licensee MDPI, Basel, Switzerland.

This article is an open access article distributed under the terms and conditions of the [Creative Commons Attribution \(CC BY\)](https://creativecommons.org/licenses/by/4.0/) license.

1. Introduction

1.1. Background

Large language models (LLMs) are increasingly deployed as agents that can access external tools and data sources, including email clients, file stores, banking and booking APIs, and web browsers. By reading external content and taking actions on a user's behalf, these systems can support more complex workflows than chat-only applications. However, this expanded capability also increases exposure to untrusted content.

Indirect prompt injection (IPI) occurs when an attacker places instructions within content that an agent is expected to process, such as a document, email, web page, or transaction record. The instructions are intended to influence the agent's behavior despite not originating from the user or system developer. Unlike a direct jailbreak, where an adversary interacts with the model directly, an indirect prompt injection is delivered

through data that the agent processes while completing a legitimate task [1–4]. This attack pattern has been demonstrated in LLM-integrated applications and agentic settings [5,6].

1.2. Problem Statement

A financial workflow illustrates the potential impact. An agent that reconciles transactions may need to read records produced by external parties. If a record includes an instruction intended to impersonate the user or redirect an action, the agent may be influenced while processing otherwise relevant task information. The practical impact depends on the actions available to the agent, the safeguards governing those actions, and whether the injected instruction changes the agent's behavior.

Related forms of exposure have been considered in retrieval-augmented systems, where untrusted passages can enter model context, in tool-using or recommender systems, where model outputs may affect external actions [5–11], and in high-consequence domains such as clinical decision support, where injected instructions embedded in patient-facing content have been shown to alter model-provided medical advice [12]. These settings motivate evaluations that consider not only whether an attack succeeds, but also the capabilities retained by an agent and the operational consequences of applying a defense.

1.3. Research Gap

Assessments of the defenses against indirect prompt injection largely focus on attack success rates or detection performance [2,5,6]. While both criteria are meaningful, they alone do not allow one to establish whether the defense ensures the preservation of capabilities of an agent needed to successfully complete the task. This means that an observed lower attack success rate can either mean that the attack was detected or disrupted by a defense, or that an agent did not reach the corresponding action because of a defense or was constrained by an action space insufficient to complete the task. Therefore, security outcomes need to be considered alongside benign utility, utility under attack, available actions and effects of a defense.

The second issue is replication and variability of low-frequency outcomes. Attack success events happen infrequently in many agentic benchmarks; hence, a single execution can make a difference for a security outcome, depending on specific tasks, model behavior and execution conditions sampled. Replication is needed to differentiate a single occurrence from a systematic outcome and to estimate the level of variance involved in infrequent attack events.

Thirdly, feasibility-aware analysis of the results is needed, since variations in observed attack success rates can stem from a number of factors, such as the model, the defense, the set of available actions, the feasibility of the attack goal or interactions between these factors. In particular, a model cannot complete an attack objective if the model cannot execute this objective in the available environment with available tools/actions. Cross-model ASR comparisons are misleading in such cases and, thus, need to be controlled through a dedicated evaluation protocol.

In order to deal with these problems, the current paper utilizes a feasibility- and capability-aware evaluation protocol designed specifically for agentic models under indirect injection. It provides separate information on attack success, benign utility, utility under attack, action and tool availability, operation effects and run-to-run variation, and separately checks whether the attack goals are feasible for the model. Feasibility-conditioned ASR is then used, where possible, to interpret attack success for goals that are feasible for the model. This is an empirically designed protocol for a particular study and benchmark and not a generalized security utility protocol.

1.4. Research Questions

This study addresses four research questions:

RQ1 (baseline attack success): What raw attack success rates are observed for indirect prompt injection against undefended tool-using agents in the evaluated benchmark, and how should cross-model differences be interpreted when benchmark goal feasibility differs across model configurations?

RQ2 (defense outcomes): How do the evaluated defense configurations affect observed attack success relative to the undefended configuration?

RQ3 (utility cost): How do the evaluated defenses affect benign-task utility and the agent's ability to complete legitimate requests?

RQ4 (security–utility trade-off): When attack outcomes, utility, action availability, and repeated-run variation are considered together, what trade-offs are observed across the evaluated defenses and models?

1.5. Contributions

The contributions made by this paper include the following.

Capability- and feasibility-aware assessment: An assessment protocol, tailored to this study and implemented for the tool-using LLM agents, which evaluates the success of the attack alongside the benign utility, utility under attack, goal feasibility, action/tool availability, operational effects, replication variance, and statistical evidence, is provided. The value of this contribution comes in explicitly accounting for and interpreting all of these dimensions in the case of indirect prompt injection in an agentic tool-using setting, instead of simply evaluating the security and utility of LLMs in a generic way.

Security interpretation conditioned on feasibility: This paper differentiates between raw ASR and attack success rates on goals that can be realistically achieved by the tested model using the matched canaries and attacks whenever possible. The rationale behind this method is to avoid potential misinterpretation of a low raw ASR due to the impossibility of achieving the attack goals as evidence of strong resistance to injection by the model itself.

Capability and action space evaluation: Whether increased security corresponds to reduced capability or narrowed-down action/tool availability is assessed. Specifically, the Tool Filter results are interpreted as an action space intervention instead of an indication of increased resistance to injection by the underlying LLM.

Evidence considering replication and statistics: This includes descriptive results and confidence intervals per run and pooled together, matched paired tests when applicable, multiple comparisons correction, and run-to-run variance, with appropriate warnings for a low number of attacks and repeated benchmarks used.

Deployment-oriented interpretation: The security findings are connected to the utility, feasibility, action availability, and operational effects of the deployment scenario under consideration, without making any universal claims about the optimality of the defense or evaluation method.

1.6. Paper Structure

Section 2 reviews indirect prompt injection, agent-targeted attacks, defenses, and benchmarks. Section 3 presents the threat model. Section 4 describes the experimental setup, including the benchmark, models, defenses, metrics, replications, and statistical analyses. Section 5 reports the results. Section 6 interprets the findings in relation to the research questions. Section 7 discusses limitations, and Section 8 concludes.

2. Related Work

2.1. Indirect Prompt Injection and Its Foundations

Greshake et al. were the first to frame indirect prompt injection as a real threat to LLM-integrated applications, demonstrating that content planted in retrieved or displayed text could steer a model with no direct access to it [1]. Later work pinned the problem down and built the first benchmarks and defenses: Yi et al. characterize a family of indirect attacks and evaluate countermeasures on integrated models [2], and broader surveys distinguish the direct channel from the indirect one and map the attack surface [3,4]. Those studies establish the threat we study. Our step is to quantify it, with matched utility costs and in a fully agentic tool-using setting, not on single-turn text.

2.2. Prompt Injection and Agent-Targeted Attacks

The attack literature has grown quickly. Some of it is optimization- or learning-driven: Neural Exec learns execution triggers that survive realistic processing [13], poisoning at the alignment stage makes downstream injections stronger [14], and the increasingly common “LLM-as-a-judge” pattern has drawn its own attacks [15]. The rest widens the channel, including visual and layout-based injections [16], payloads built from mathematical functions to dodge filters [17], and adversarial inputs riding in through game or application text [18]; the surface keeps expanding. Most directly related to our setting, CheatAgent turns an LLM agent itself into the attacker against a recommender system [7,19], underscoring that agentic pipelines are both targets and tools. We do not propose a new attack; we adopt AgentDojo’s strongest built-in attack so that our defense comparison rests on a validated, reproducible adversary.

2.3. Defenses and Detection

Indirect prompt injection defenses can be grouped into several broad families. Boundary-marking or “spotlighting” approaches delimit untrusted content in an effort to distinguish data from instructions [20]. Detection-based approaches use classifiers to identify potentially injected content before or during agent processing; PromptShield targets deployable detection [21], and MalPID provides a labeled dataset for this task [22]. Transformation-based approaches paraphrase or re-translate inputs in an attempt to disrupt crafted triggers [23,24].

This study evaluates selected representative defense configurations and reports their observed attack outcomes together with benign-task utility, utility under attack, action restrictions, and repeated-run outcomes. The purpose is not to establish a complete ranking of defense families, but to show how these measures affect the interpretation of a defense configuration in the evaluated benchmark.

Recent work further considers the agentic setting through tool-result parsing [25], inference-time correction [26], causal attribution over tool invocations [27], adaptive tool-based attacks [28], and agentic red teaming [29]. These approaches intervene at different points in the agent pipeline: some aim to identify or modify untrusted content during execution, whereas others examine or constrain the actions available to the agent. Our study does not compare its selected defenses directly with all of these approaches. Instead, it evaluates a fixed set of defense configurations and reports the security, utility, action restriction, and replication information needed to interpret observed changes in attack success.

2.4. LLM Agents, Benchmarks, and Security Evaluation

Agent benchmarking has grown alongside agent deployment. A recent survey reviews emerging trends across LLM agent benchmarks [30]. Benchmarks have also been built for

particular deployment settings: agents that consume live sensor data [31], agents operating in immersive environments [32], and agents that plan cyber attack and defense tactics [33]. The first and third involve the untrusted external input studied here, but none of these benchmarks report attack success together with benign task utility, which is the combination this study evaluates. Within this space, AgentDojo [5] is distinctive for coupling realistic multi-step tool tasks with built-in attacks and a deterministic security/utility scorer, which is precisely what a controlled defense comparison needs. We build our study on its banking suite for that reason.

Benchmarking efforts have also examined indirect prompt injection in tool-integrated agents. InjecAgent evaluates vulnerability across a fixed collection of tool-based tasks and adversarial scenarios, whereas AgentDojo provides a dynamic environment for evaluating attacks, defenses, benign utility, and utility under attack [5,6]. These benchmarks motivate multi-outcome reporting but do not by themselves establish that a defense is generally effective across models, tasks, or adaptive attack settings.

2.5. Jailbreaking, Retrieval Poisoning, and the Broader Safety Context

Indirect injection sits alongside two adjacent threats. Jailbreaking manipulates the model's own inputs to bypass alignment—through visual examples [34], stylistic rewriting [35], or multimodal distraction [36]—and differs from our setting in that the adversary speaks to the model directly. Retrieval-augmented generation introduces a data channel much like an agent's tool outputs, and a line of work studies poisoning of that channel and its mitigation [8–11]. Three surveys of LLM safety and prompt injection defense provide the broader context for this work [37–39]. Because every defense evaluated here operates through the prompt or the tool interface rather than through retraining, work on prompt engineering is also relevant [40]. The consequences of a successful injection depend on the domain and on the actions an agent is permitted to take, a point illustrated by a survey of ethical issues in deploying LLM agents in biomedicine [41]. LLMs are also deployed defensively in security work: building threat-intelligence knowledge graphs [42], analyzing vulnerabilities in medical devices [43] and embedded systems [44], detecting insider threats [45], reasoning over static application security testing reports [46], and as security-specialized models [47]. These systems read untrusted artifacts such as reports, logs and third-party documents, so they are themselves exposed to the injection channel measured in this study. That exposure is what makes the security and utility trade-off reported here consequential in practice.

2.6. Positioning of This Work

Relative to the work reviewed above, this study has three main features. First, while attack studies often introduce or optimize new injection methods [13–17], and defense studies frequently report attack-blocking or detection outcomes [21–24], this study evaluates selected defense configurations while reporting observed attack success together with benign utility and utility under attack. This makes the operational cost of a defense visible alongside its observed security outcome.

Second, this study applies the same evaluation protocol to three tool-using model configurations on the selected agent benchmark [5]. This design enables comparison of observed outcomes across the evaluated configurations, although differences cannot be attributed solely to the model or the defense because task reachability, available actions, and other interactions may also affect the results.

Third, this study examines the relationship between defense outcomes, utility cost, action availability, and repeated-run variation. Rather than treating a lower observed attack

success rate as sufficient evidence of a preferable defense, it interprets that outcome together with the agent's ability to complete legitimate tasks and the scope of the intervention.

The closest concurrent efforts target agent-specific defense at the tool-result or inference-time level [25–27]. Our contribution is complementary: it does not provide a direct head-to-head comparison with all such approaches or claim a novel general-purpose evaluation framework. Instead, it offers an empirical reporting approach for the selected benchmark and defense configurations, designed to make security outcomes, utility costs, action restrictions, and replication limits explicit.

3. Threat Model

In this study, we assume an attacker who can manipulate only the third-party content consumed by the agent during execution of a legitimate task, such as a transaction record, a document, or a tool-returned web page. The attacker is not assumed to control the user instruction, the system prompt, the tool interface, or the model parameters. Under this threat model, the malicious instruction reaches the agent through untrusted data rather than through the trusted instruction path. We define a successful attack as one in which the agent executes the attacker's injected objective, regardless of whether it also completes the user's intended task. This distinction is important because the most concerning real-world failure is not an obvious breakdown, but a covert one in which the agent satisfies the user request while simultaneously advancing the attacker's goal. The experimental design described in Section 4 is intended to evaluate agent behavior under precisely this setting.

4. Materials and Methods

This paper reports a controlled benchmark evaluation of selected defenses against indirect prompt injection in tool-using LLM agents. This study applies a study-specific evaluation protocol that reports security outcomes, legitimate-task utility, action restrictions, operational measures, goal feasibility, and run-to-run variation under controlled benchmark conditions. This study reports security–utility trade-offs and run-to-run variation for the selected benchmark and evaluated configuration.

All experiments are carried out with the help of the AgentDojo benchmark platform for autonomously evaluating the performance of LLM agents while interacting with external tools. This research study evaluates three frontier LLMs under identical experimental settings in terms of attacks performed, evaluation metrics used, and statistical analyses conducted while the agents use and do not use representative defense mechanisms.

4.1. Experimental Workflow

To conduct a transparent and reproducible empirical evaluation of defenses against indirect prompt injection attacks, this study uses a structured experimental protocol comprising standardized benchmarking, controlled experimentation, multidimensional outcome reporting, statistical analysis, and replication analysis. The protocol reports security and operational utility measures together rather than relying only on attack success outcomes. It is used to characterize the observed trade-offs within the evaluated benchmark and is not presented as a new evaluation methodology.

Figure 1 summarizes the seven stages of the experimental protocol. First, the indirect prompt injection threat model is specified, including the assumed attacker capabilities and security objectives. Next, the experimental setup is established using the AgentDojo banking benchmark, and the models are evaluated under the selected defense configurations. Each evaluated model–defense configuration is assessed using the security–utility reporting protocol, which records the attack success rate (ASR), benign utility (BU), utility

under attack (UUA), and response latency. Finally, the results are analyzed, and outcomes from repeated benchmark runs are compared to describe observed run-to-run variation.

Evaluation protocol and analysis workflow used in this study

Study-specific reporting of security, utility, action restrictions, and run-to-run variation




Figure 1. Evaluation protocol and analysis workflow used in this study. The protocol evaluates indirect prompt injection in the AgentDojo banking benchmark using the selected models and defense configurations. It reports attack success rate, benign utility, utility under attack, action availability, and run-to-run variation. The workflow supports benchmark-specific interpretation and does not define a universal defense ranking. The workflow diagram lists task-cluster bootstrap as an approach considered during method planning; it was not adopted in the reported statistical methods, which are described in Section 4.7 and rely on Wilson intervals and paired McNemar tests.

Rather than interpreting attack success alone, the protocol reports the effects of each defense configuration on both security outcomes and legitimate task completion. Reporting ASR, BU, and UUA together helps identify cases in which a lower observed ASR occurs alongside reduced task completion or restricted action availability. Repeated benchmark runs provide descriptive evidence of run-to-run variation and help prevent an isolated execution from being interpreted as a stable result.

Table 1 below gives a summary of the experimental design used in this research. As independent variables, the evaluated LLM models and defense mechanisms are used, while the multi-dimensional performance indicators (ASR, BU, UUA, and response latency) represent the dependent variables. To guarantee comparability of all the experiments, benchmark configurations, prompt templates, decoding options, model snapshots, and the procedures of the evaluations are used as the controlled variables.

Table 1. Experimental variables.

Category	Variables
Independent variables	LLM model and defense strategy
Dependent variables	Attack success rate (ASR), benign utility (BU), utility under attack (UUA), and response latency
Controlled variables	AgentDojo v0.1.35, banking benchmark, <i>important_instructions</i> attack, temperature = 0, fixed prompts, pinned model versions, deterministic tool environment, and statistical confidence level (95%)

In summary, the evaluation method incorporates standardized benchmarking, multi-faceted result presentation, goal feasibility testing, action space examination, statistics, and replication into the process of interpreting results clearly. Its unique objective in this study is to ensure that the ASR does not get interpreted independently of actionable feasibility. The method applies only to the chosen defenses, models, benchmark, attacks, and experiments, and it is not suggested as a universal approach for security–utility analysis.

4.2. Attack Scenario

The threat model and attacker capabilities are defined in Section 3. Unlike in the case of direct prompt injection, where the adversary provides malicious instructions directly to the LLM model, indirect prompt injection attacks include embedding the adversarial instructions into untrusted information sources such as emails, web pages, documents, transaction records or retrieved knowledge. As a result of accessing such untrusted information during execution of the task by the tool using an LLM agent, the hidden instruction may affect the behavior of the model.

The adversary is assumed to have the following capabilities:

- Access to one or multiple external information sources used by the agent.
- Embedding natural language instructions in the legitimate information sources.
- Knowledge about the tool use capabilities of the agent and absence of access to the model parameters, system prompt and infrastructure of the provider.

On the contrary, the adversary does not have the following capabilities:

- Modification of the underlying LLM model.
- Intercepting the API requests.
- Getting confidential user credentials.
- Influencing the benchmarking scoring procedure.

Evaluation is focused on realistic scenarios when the autonomous agent retrieves information from external information sources before executing tool commands, such as financial operations, retrieving information and managing accounts. This threat model is very close to emerging real-life threat scenarios involving agentic AI, as the adversary can embed malicious instructions in the benign content, influencing the decision-making process.

To conduct standardized experiments across all experiments, attacks are performed using the important instructions scenario provided by the AgentDojo benchmark. The attack scenario was confirmed by the AgentDojo benchmark as the most effective out-of-the-box scenario of indirect prompt injection due to its imitation of the user in the retrieved content and attempts to change the initial objective of the user through high-priority instructions. Using standard attacks helps to eliminate the impact of custom payloads and enables fair comparison across different defense approaches and LLM models.

4.3. Benchmark and Experimental Environment

The experiments involved AgentDojo (version 0.1.35), which is a peer-reviewed benchmark specifically designed to evaluate the security properties of tool-using LLM agents. The benchmark provides a standardized experimental environment that includes realistic user tasks, adversarial prompt injection scenarios, deterministic tool execution and evaluation measures, allowing us to conduct reproducible research on security issues.

The banking application domain was selected, since banking assistants can be considered one of the riskiest application scenarios for autonomous LLM agents. Financial assistants process sensitive information and perform critical actions, such as account management, checking balances, performing transfers of funds and verifying transactions. As a result, a successful single indirect prompt injection attack on this type of agent can have

significant security and financial implications. Thus, the banking application domain is the appropriate application to evaluate the effectiveness of the defenses.

The banking benchmark contains 16 legitimate user tasks and 9 indirect prompt injection tasks. Every legitimate task is combined with every injection scenario, producing 144 attack cases for each combination of model and defense approach. Also, the 16 legitimate user tasks are performed without injection to provide a benign baseline for measuring utility. Such an experimental design allows us to test the resistance to attacks and ability to perform normal tasks in the same environment.

To ensure experimental consistency, all the LLM models under analysis interact with the same environment of the benchmark, the same tool interface, the same prompt and the same tasks. The models' snapshots, version of the benchmark, software dependencies and decoding parameters are preserved during experiments to minimize external sources of variation. The deterministic execution environment provided by the AgentDojo benchmark increases the internal validity of the experiment, as differences in performance are caused only by the evaluated models and defense mechanisms.

The combination of the benchmark, realistic application domain, consistent execution environment and reproducible experimental protocol provides a solid basis for the systematic evaluation of the security–utility trade-off of defenses against indirect prompt injection in tool-using LLM agents.

4.4. Evaluation of LLM Models

In this study, three frontier LLM models that allow autonomous tool invocation using commercial APIs are tested: GPT-5.4 (gpt-5.4-2026-03-05), GPT-5.4-mini (gpt-5.4-mini-2026-03-17), and Claude Sonnet 4.6 (claude-sonnet-4-6). Such models were chosen as examples of different levels of capability of state-of-the-art foundation models that offer adequate tool-calling capabilities suitable for agentic applications.

Two different providers serve as sources of the models used in this study, thus decreasing the probability of the experiment results being biased towards the proprietary architecture. GPT-5.4 represents the frontier reasoning model that was designed to operate autonomously with high accuracy. Meanwhile, GPT-5.4-mini is a computationally efficient model deployed at low cost. Claude Sonnet 4.6 provides an example of an independently developed frontier architecture, thus allowing for comparison of the provider architectures under the same benchmark conditions.

To broaden coverage across model families and providers, this study includes models from two providers under the same benchmark conditions. All GPT models were executed via the pipeline provided by AgentDojo's OpenAI service, while Claude Sonnet 4.6 was evaluated via the corresponding pipeline provided by Anthropic. To keep the experimental conditions consistent, all models were run using deterministic decoding with a temperature of zero. For the GPT models, reasoning effort was disabled, thus invoking tools only using the Chat Completions interface available in AgentDojo.

To control the variability in the experiments performed, the model snapshots, API versions, decoding settings, benchmark versions, prompt templates, and software dependencies were kept constant throughout this study.

4.5. Evaluated Defense Mechanisms

Five agent configurations were evaluated: an undefended control and four defense mechanisms. The evaluated defenses represent prompt structuring, instruction reinforcement, learned prompt injection detection, and tool-access restriction. The same benchmark tasks, attack templates, and model-specific settings were used across the applicable configurations.

No Defense (Control): The control configuration used the benchmark agent without an additional prompt injection defense. It provides the baseline values for the attack success rate (ASR), benign utility (BU), utility under attack (UUA), and operational measures.

Spotlighting: Spotlighting is a prompt-structuring defense that marks retrieved or tool-returned content as external data by wrapping it with explicit delimiters. The intended purpose is to make the distinction between trusted instructions and untrusted retrieved content explicit in the prompt context.

Repeat User Prompt: This defense repeats the original user request after external content has been added to the prompt. The mechanism reinforces the user's stated task within the agent context without introducing an additional detection model or restricting the available tools.

Prompt Injection Detector: The evaluated PI Detector was AgentDojo's TransformersBasedPIDetector configured with the protectai/deberta-v3-base-prompt-injection-v2 classifier. The detector was applied separately to each textual tool output message in message mode. It used the SAFE label and a decision threshold of 0.5; a tool output was classified as an injection when its computed safety score was below this threshold.

The detector was configured with `raise_on_injection = False`, which was the default behavior because no alternative value was passed during instantiation. Consequently, a detected injection did not abort the agent episode. Instead, the textual content blocks of the flagged message were replaced in place with the literal placeholder "<Data omitted because a prompt injection was detected>". Non-text content blocks, if present, were retained. The edited message remained in the conversation at its original position, and the agent continued execution with the placeholder rather than the original textual tool output.

The detector implementation specified the Hugging Face model repository identifier but did not provide a revision argument or commit hash. Therefore, the exact classifier revision was not pinned in the experimental code. This limits exact reconstruction of the detector dependency if the upstream repository changes after the experiment.

Tool Filter: The Tool Filter was evaluated only for the OpenAI models. Before the main agent model was called, a separate OpenAI function-calling step received the currently available tool definitions and a prompt instructing it to retain only tools relevant to the user task. For each available runtime function, the filter checked whether its tool name appeared in the filtering model's text output and retained the matching functions. The runtime tool list was then updated so that only those retained functions were supplied to the main agent call. The filter, therefore, restricted action availability by reducing the tool set available for subsequent execution. Because this implementation depends on the OpenAI function-calling pipeline, it was not evaluated for Claude Sonnet 4.6.

These configurations were evaluated using the joint security–utility protocol described in the following section. Their observed outcomes are interpreted using ASR, BU, UUA, reproducibility results, and operational measures rather than attack success outcomes alone.

4.6. Capability- and Feasibility-Aware Outcome Evaluation

The joint evaluation of security and utility performance is a well-established methodology and is not presented as a novel methodology in this work. The specific contribution of this study is in making attack success comprehensible against the backdrop of the capabilities and limitations of tool-using agents under indirect prompt injection. We consider the security and legitimate utility, feasibility, action/tool availability, operational effects, run-to-run variation, and statistical uncertainty of each evaluated model–defense combination.

Three basic outcome metrics for each evaluated model–defense combination include attack success rate (ASR), benign utility (BU), and utility under attack (UUA). The following

supplementary metrics include goal-completable canaries, action/tool availability, response latency, tool-call counts, run-to-run variation, 95% Wilson confidence intervals, and paired comparisons where matched traces are available. The produced evidence characterizes the security–utility trade-off and feasibility-conditioned attack outcomes for the tested benchmark; this work makes no claims on the optimality of the tested defense or any other general-purpose evaluation methodology.

The ASR is defined as the ratio of successful attacks in Equation (1):

$$ASR = \frac{N_{\text{attack}}^{\text{success}}}{N_{\text{attack}}} \quad (1)$$

where

- $N_{\text{attack}}^{\text{success}}$ is the number of attack instances in which the attacker successfully achieves the malicious objective.
- N_{attack} is the total number of evaluated attack instances (144 for a single run and 288 for the pooled two-run analysis).

Benign utility is the ratio of the number of successfully completed benign tasks in Equation (2):

$$BU = \frac{N_{\text{benign}}^{\text{success}}}{N_{\text{benign}}} \quad (2)$$

where

- $N_{\text{benign}}^{\text{success}}$ is the number of benign tasks completed successfully.
- N_{benign} is the total number of benign evaluation tasks (16).

Utility under attack is the ratio of the number of legitimate user tasks completed successfully despite attack attempts in Equation (3):

$$UUA = \frac{N_{\text{attack}}^{\text{success under attack}}}{N_{\text{attack}}} \quad (3)$$

where

- $N_{\text{attack}}^{\text{success under attack}}$ is the number of attack instances in which the agent still completed the legitimate user task; and
- N_{attack} is the total number of attack instances.

The feasibility-conditioned attack success is reported descriptively as the share of attacks achieving the objective out of those attacks whose goal was proved feasible in the corresponding canary run. In formulas, $ASR_{\text{feasible}} = N_{\text{success,feasible}}/N_{\text{feasible}}$, where N_{feasible} is the number of attack instances targeting goals demonstrated as feasible by the model in the corresponding canary evidence. This metric is not an alternative to raw ASR; this is a sensitivity measure conditioned by the agent’s capabilities and feasibility that allows us to separate attack resistance from the inability to achieve an otherwise required goal.

The goal-completable canary runs were used to check whether the injection goal could be accomplished by the agent under open conditions when it was a part of an ordinary user’s task. The canary runs are not related to the definitions of ASR, BU, or UUA and do not represent defense-specific outcomes. They show whether the attack goal is feasible for the model and, where there is matching trace data, serve as a basis for the feasibility-conditioned analysis reported in Section 5.2. The action/tool availability and operational behavior are separately evaluated because the defense mechanism can make the attacks less successful by limiting the space of executable actions.

Response latencies, tool-call counts, and zero-tool-call rates were collected for the attack instances in each of the evaluated model–defense combinations with available tracebacks. These operational metrics are reported in Section 5.7. Since latency depends on many factors, such as the model provider, service conditions, tool environment, benchmark tasks, and defense mechanism itself, the presented metrics are treated as model–defense-specific measurements.

For each reported proportion, 95% Wilson confidence intervals are reported. For the pooled two-run counts, these intervals are descriptive summaries of the observed proportions and not the correlation-aware inferential intervals. As the same benchmark instances were repeated in the runs, a pooled Wilson interval can be narrower than the interval explicitly accounting for the correlation. The per-run results are separately reported where appropriate to reveal run-to-run variation. The formal paired inference, where possible, is described in Section 4.7.

4.7. Statistical Analysis

The statistical analysis distinguishes descriptive summaries from paired inferential comparisons. ASR, BU, and UUA are reported for each evaluated configuration, together with 95% Wilson confidence intervals. The results from repeated benchmark runs are shown separately. Where pooled counts are reported, they summarize the two observed runs descriptively and are not interpreted as independent observations.

Paired hypothesis tests were conducted for GPT-5.4-mini run 2, for which 144 matched attack-level records were analyzed. Matched run-2 traces were also available for GPT-5.4 and Claude Sonnet 4.6; however, each model’s undefended baseline recorded 0/144 attack successes in run 2, yielding no discordant attack outcomes for an exact McNemar comparison.

Table 2 summarizes the statistical procedures used in this study.

Table 2. Statistical methods used in the experimental evaluation.

Statistical Method	Purpose	Applied to	Interpretation
Wilson 95% confidence interval	Describe uncertainty around observed proportions	ASR, BU, and UUA	Reported for each configuration. For pooled two-run counts, intervals are descriptive because benchmark instances were repeated.
Exact McNemar test	Compare paired binary attack outcomes between a defense and the undefended baseline	Trace-backed GPT-5.4-mini defense-versus-baseline comparisons	Tests whether discordant paired attack outcomes differ between the baseline and defense configuration.
Holm multiple-comparison correction	Control the family-wise error rate across the four paired GPT-5.4-mini defense comparisons	Exact McNemar p -values for GPT-5.4-mini	Adjusted p -values are used for the stated statistical decision criterion.

4.7.1. Confidence Interval Estimation

For each evaluated model–defense configuration, ASR, BU, and UUA are reported with 95% Wilson confidence intervals. Wilson intervals were selected because they remain well-behaved when observed proportions are close to zero or one, unlike the standard Wald interval, which can perform poorly at such boundaries [48].

For a single run, the interval describes the observed proportion among the evaluated benchmark instances. For pooled two-run counts, the interval is reported as a descrip-

tive summary of the pooled count and should not be interpreted as accounting for the dependence created by re-evaluating the same benchmark instances.

4.7.2. Paired Hypothesis Testing

Exact McNemar tests were used for the GPT-5.4-mini run 2 comparisons between each defense configuration and the undefended baseline [49]. Attack outcomes were paired by user-task identifier and injection-task identifier, yielding 144 matched attack instances for each available comparison. The test evaluates the imbalance between instances for which the defense prevented an attack that succeeded under the baseline and instances for which an attack succeeded under the defense but not under the baseline.

Four defense-versus-baseline comparisons were evaluated for GPT-5.4-mini run 2. Their p -values were adjusted using the Holm procedure [50] to control the family-wise error rate within this comparison family. The paired analysis was not extended to GPT-5.4 or Claude Sonnet 4.6 because each model's undefended baseline recorded 0/144 attack successes in run 2, yielding no discordant pairs and leaving the exact McNemar test without power for those models.

4.7.3. Statistical Decision Criteria and Scope

For the trace-backed GPT-5.4-mini paired analysis, statistical significance was assessed at $\alpha = 0.05$ using Holm-adjusted McNemar p -values. A result was considered statistically significant only when its Holm-adjusted p -value was below 0.05.

Wilson confidence intervals are not used as substitute hypothesis tests. In particular, overlap or non-overlap of separate Wilson intervals is not used as a decision rule for defense effectiveness.

All statistical conclusions are limited to the available benchmark data and analysis scope. Low event counts, a baseline ASR near zero, repeated evaluation of the same benchmark instances, incomplete trace availability, and differences in action availability limit the precision and generalizability of the comparisons. Security outcomes must, therefore, be interpreted together with benign utility, utility under attack, action restrictions, and the replication structure.

4.8. Reproducibility and Experimental Validity

LLM agent outcomes can vary across nominally similar executions because of provider-side variation, model-serving conditions, and other sources of run-to-run variability. This study, therefore, includes two independent benchmark replications for every evaluated model–defense configuration. The replications are used to describe the stability of and variation in the observed security and utility outcomes within the evaluated benchmark setting.

4.8.1. Experimental Reproducibility

Each model–defense configuration was executed using the automated AgentDojo evaluation pipeline. A single execution of a configuration comprised 144 attack instances and 16 benign-task evaluations. Attack traces recorded the user task, injection goal, defense configuration, agent outcome, tool invocations, and benchmark score where trace retention was available. Goal-completeness canary evaluations were conducted separately as honest-goal checks and were not part of every model–defense benchmark execution.

The available archived canary records comprise seven canary replications per goal for GPT-5.4, thirteen per goal for GPT-5.4-mini, and six per goal for Claude Sonnet 4.6. These counts differ because the canaries were accumulated across separate canary sessions and available trace records, rather than being fixed at two benchmark executions per configuration.

The benchmark version, configured model identifier, prompt templates, tool definitions, temperature setting, reasoning configuration, software environment, and evaluation procedure were held constant across the two replications of each configuration. The experiment outputs, available traces, and summary results were retained in the project record to support verification of the reported results.

Trace availability was not uniform across the first frontier-model run because of a historical logging defect. Seven of the nine applicable GPT-5.4 and Claude Sonnet 4.6 first-run configurations remain available only as summary results. Two first-run Repeat User Prompt configurations were subsequently recovered through trace fingerprinting. All evaluated frontier configurations were executed in two independent runs under the same evaluation settings. The rerun refers to replication 2, reported in Section 5.5; thus, every evaluated configuration has exactly two executions, and at least one execution is trace-backed. The implications of this trace record are discussed further in Sections 5.5 and 7.

4.8.2. Experimental Replication

The benchmark was executed twice for each of the 14 evaluated model–defense configurations. The two OpenAI models each included five configurations: the undefended control, Spotlighting, Prompt Injection Detector, Tool Filter, and Repeat User Prompt. Claude Sonnet 4.6 included four configurations: the undefended control, Spotlighting, Prompt Injection Detector, and Repeat User Prompt. Tool Filter was not evaluated for Claude Sonnet 4.6 because the implemented mechanism relied on the OpenAI function-calling interface.

The replication design and evaluation counts for every model–defense configuration are summarized in Table 3.

Table 3. Replication design and benchmark evaluation counts by model–defense configuration. Each configuration was evaluated in two independent benchmark runs. Each run comprised 144 attack instances and 16 benign-task evaluations. Pooled counts describe the total benchmark evaluations across the two runs; they do not imply independent observations because the same benchmark tasks and attack instances were evaluated repeatedly.

Model	Defense	Runs	Attack Instances per Run	Pooled Attack Instances	Benign Tasks per Run	Pooled Benign Tasks
GPT-5.4	None (control)	2	144	288	16	32
GPT-5.4	Spotlighting	2	144	288	16	32
GPT-5.4	PI detector	2	144	288	16	32
GPT-5.4	Tool filter	2	144	288	16	32
GPT-5.4	Repeat prompt	2	144	288	16	32
GPT-5.4-mini	None (control)	2	144	288	16	32
GPT-5.4-mini	Spotlighting	2	144	288	16	32
GPT-5.4-mini	PI detector	2	144	288	16	32
GPT-5.4-mini	Tool filter	2	144	288	16	32
GPT-5.4-mini	Repeat prompt	2	144	288	16	32
Claude Sonnet 4.6	None (control)	2	144	288	16	32
Claude Sonnet 4.6	Spotlighting	2	144	288	16	32

Table 3. *Cont.*

Model	Defense	Runs	Attack Instances per Run	Pooled Attack Instances	Benign Tasks per Run	Pooled Benign Tasks
Claude Sonnet 4.6	PI detector	2	144	288	16	32
Claude Sonnet 4.6	Repeat prompt	2	144	288	16	32

Note: Tool Filter was not evaluated for Claude Sonnet 4.6 because the implemented mechanism relied on the OpenAI function-calling interface. Table 3 reports attack and benign-task benchmark evaluation counts only. It does not indicate complete first-run trace availability; the trace availability limitation and the surviving Repeat User Prompt traces are described in Section 4.8.1.

Goal feasibility was assessed separately using AgentDojo’s honest-goal canary procedure, in which each injection goal was evaluated as an ordinary user request. The canary was not part of every model–defense benchmark run and should not be interpreted as a defense-specific repeated outcome. The feasibility analysis is reported separately and is limited by the available canary evidence.

Each run used the same benchmark tasks and configuration-specific evaluation procedure. Run-level ASR and BU outcomes are reported separately in Section 5.5 to make observed variation visible, and robust across-run summary statistics (e.g., medians or cluster bootstrap intervals) are not estimated because each cell has only two replications. Where results from both runs are combined, pooled counts are reported as descriptive summaries. Because the same benchmark instances were evaluated in both runs, pooled counts and their Wilson intervals should not be interpreted as independent observations or as correlation-aware inferential estimates.

The two replications provide evidence about variation within the evaluated benchmark, model configurations, defense implementations, and execution conditions. They do not establish that the same outcomes will be reproduced across different task suites, attack families, model versions, providers, prompts, tool environments, or deployment settings.

4.8.3. Experimental Validity

Internal validity was supported by holding the benchmark version, task set, prompt templates, tool definitions, temperature setting, model configuration, and evaluation procedure constant within each replicated configuration. These controls support comparison of the evaluated configurations, although they do not eliminate provider-side variation or other unobserved sources of run-to-run variability.

Construct validity was supported by reporting multiple outcome measures rather than ASR alone. This study reports the ASR, BU, UUA, goal-completeness canary outcomes, and operational measures. These measures distinguish observed attack outcomes from legitimate task completion and tool-use behavior. However, they remain operationalizations within the AgentDojo banking benchmark and should not be treated as complete measures of model security or deployment utility.

Statistical conclusion validity was addressed by reporting Wilson confidence intervals, separately reporting run-level outcomes, using exact paired McNemar tests only where matched trace data were available, and applying Holm correction within the GPT-5.4-mini paired-comparison family. Low event counts, repeated benchmark instances, and incomplete trace availability limit the precision of the statistical comparisons. Accordingly, pooled intervals are not interpreted as substitutes for paired inferential tests. Since each experimental cell is tested through only two replications that are independent of one another, the replications are insufficient to make any strong conclusions about the stochastic

nature of LLM performance. For this reason, the current research views variations from run to run and pooled ASR variations primarily as descriptive evidence.

External validity is limited using one benchmark domain, one indirect prompt injection attack family, the evaluated model versions, the selected defense implementations, and the available tool environments. This study provides evidence about these configurations under the evaluated conditions; it does not establish general defense effectiveness across other agentic domains, benchmarks, attacks, models, or deployment settings.

5. Results

The following section reports the empirical outcomes of indirect prompt injection attacks and the evaluated defense configurations using the joint security–utility reporting protocol applied in this study. Rather than relying on attack success rate (ASR) alone, the analysis reports ASR together with benign utility (BU), utility under attack (UUA), operational measures, action restrictions, goal feasibility, and run-to-run variation. Such multi-faceted analysis can help provide a more complete assessment of various defense mechanisms by understanding if any observed improvements in security are a result of effective attack mitigation or a loss of benign utility of the agent.

The results are grouped based on the research questions identified in Section 1. In the first place, baseline vulnerabilities of frontier tool-using LLM agents are considered to understand how inherently resilient the contemporary models are to indirect prompt injection attacks (RQ1). Furthermore, the effectiveness of the defense mechanisms is investigated (RQ2), followed by the analysis of the utility cost of each defense and the resulting security–utility trade-off (RQ3 and RQ4), utility under attack, the operational overhead associated with deployment of defenses, and the reproducibility of the experimental results. Finally, comparative analysis of the findings offers practical recommendations for the deployment of tool-using LLM agents.

Throughout the results, the findings are interpreted within the scope of the evaluated benchmark and configurations. First, raw attack success outcomes differ across the evaluated models, but cross-model differences should be interpreted cautiously because the benchmark goals were not equally reachable for every model. Second, the observed defense outcomes must be considered together with benign utility, utility under attack, and action availability, because a lower observed attack success rate can coincide with reduced legitimate task completion or restricted tool use. Third, the two independent benchmark replications show that benign utility was generally more stable than individual low-frequency attack outcomes. The following sections report these results descriptively and identify the limitations that constrain broader conclusions.

5.1. Baseline Attack Success Under the Evaluated Benchmark (RQ1)

(RQ1): What raw attack success is observed for indirect prompt injection against undefended tool-using LLM agents in the evaluated benchmark, and how should cross-model differences be interpreted when goal feasibility differs across models?

This section reports the observed attack success outcomes for the undefended model configurations. These baseline measurements provide the reference point for the defense comparisons in Section 5.2. However, raw attack success rate (ASR) should be interpreted cautiously because the benchmark denominator includes attack goals that the acting model may not complete even when the same goal is presented openly as an ordinary user request.

Table 4 reports the raw ASR pooled over the two benchmark replications. GPT-5.4 recorded zero successful attacks out of 288 instances, GPT-5.4-mini recorded 11 successful attacks out of 288 instances, and Claude Sonnet 4.6 recorded one successful attack out

of 288 instances. The corresponding observed raw ASR values were 0.0%, 3.8%, and 0.3%, respectively.

Table 4. Raw baseline attack success rate (ASR) for undefended tool-using LLM agents in the evaluated AgentDojo benchmark. Results are pooled over two independent benchmark replications, comprising 288 attack instances per model. Wilson 95% confidence intervals are reported. Raw ASR includes all benchmark attack instances and should be interpreted alongside the feasibility-conditioned estimates in Table 5 and the goal feasibility results in Table 6.

Model	Attack Success Rate (Wilson 95% CI)	Successful Attacks
GPT-5.4	0.0% [0.0, 1.3]	0/288
GPT-5.4-mini	3.8% [2.1, 6.7]	11/288
Claude Sonnet 4.6	0.3% [0.1, 1.9]	1/288

The observed raw ASR values differed across the evaluated models. However, these differences should not be interpreted as direct estimates of intrinsic resistance to indirect prompt injection. The raw ASR combines multiple factors, including the model's response to injected instructions, its ability or willingness to complete the underlying benchmark goal, the specific prompt configuration, and run-to-run variation.

The goal completability results reported in Table 6 show that the injection goals were not equally reachable across the three models. Across all available standalone canary replications, at least one successful completion was observed for three of nine injection goals for GPT-5.4, nine of nine goals for GPT-5.4-mini, and two of nine goals for Claude Sonnet 4.6. These aggregate at-least-once completion rates characterize variation in goal feasibility across available canary replications; they do not define the matched-canary denominators used for the feasibility-conditioned ASR analysis in Table 5.

Table 5, therefore, reports feasibility-conditioned attack success outcomes for the available matched traces. These conditioned results provide additional context for interpreting the raw ASR values but remain limited by the available trace coverage, particularly for the first-run frontier-model outcomes. The raw ASR and the feasibility-conditioned estimates should be considered together rather than used to produce a universal ranking of model robustness.

The low number of observed attack successes in the GPT-5.4 and Claude Sonnet 4.6 configurations also limits the ability to estimate small defense-related changes in the ASR. In such sparse-event settings, a reduction in the observed number of successful attacks may reflect a small number of benchmark instances and run-to-run variation. Conversely, the absence of an observed attack in a finite benchmark does not establish that a model is invulnerable to indirect prompt injection.

Accordingly, the baseline results establish the observed attack outcomes for the evaluated benchmark configuration, not a general measure of inherent model security. The following section evaluates the defense configurations relative to these baseline outcomes while considering the feasibility, utility, and reproducibility limitations of this study.

5.2. Security Outcomes of Defense Mechanisms (RQ2)

(RQ2): What changes in observed attack success are associated with representative defense mechanisms under the evaluated benchmark conditions, and how should these changes be interpreted alongside goal feasibility, utility, and replication results?

This section reports the observed attack success outcomes for four representative defense mechanisms: Spotlighting, Repeat User Prompt, Prompt Injection Detector, and Tool Filter. Tool Filter was evaluated only for the OpenAI models because the implemented

mechanism relies on the OpenAI function-calling interface and was not available for Claude Sonnet 4.6.

Table 5 reports the raw ASR for each model–defense configuration and the feasibility-conditioned attack success outcomes for the available matched traces. The raw and conditioned measures should be interpreted together. The raw ASR summarizes outcomes across all benchmark attack instances, while the conditioned measure addresses the fact that models differ in whether they complete the underlying injection goals when those goals are presented as ordinary user requests.

The number of observed successful attacks was low in several configurations. Consequently, small differences in the raw ASR may reflect a limited number of attack instances and run-to-run variation. Since each experimental setup is measured with only two independent replicates, such replication is insufficient to draw meaningful inferences about the stochastic variation of large language model (LLM) behaviors. As such, the ASR differences observed must be regarded as descriptive findings rather than being conclusive evidence for the differences in defense effectiveness.

The paired tests detailed in Section 5.6 provide the statistical comparisons when the appropriate paired traces are available. No pairwise comparison survived the Holm correction, and hence, the differences should not be taken as statistically significant improvements in resistance to attacks. Security findings are discussed alongside benign utility, utility under attack, reproducibility, and goal feasibility evidence in Table 6. Sparsity of attacks and few independent replicates limit the statistical power as well. More independent replicates and more attack scenarios in the future work will provide better estimations of defense effectiveness.

5.2.1. Observed Attack Success Across Model–Defense Configurations

Table 5 reports the raw attack success rates observed for each evaluated model–defense configuration and complementary feasibility-conditioned estimates based on the available matched canary and attack traces. Together, these results show the observed outcomes while distinguishing raw benchmark rates from estimates restricted to goals that the model completed in the available canary evidence.

For GPT-5.4, the raw attack success counts were zero in the undefended, Prompt Injection Detector, Tool Filter, and Repeat User Prompt configurations, while Spotlighting recorded one successful attack out of 288 instances. For Claude Sonnet 4.6, the undefended configuration recorded one successful attack out of 288 instances, whereas the evaluated defense configurations recorded zero successful attacks in the pooled raw results. Because these configurations contain few observed attack events, the raw counts should not be interpreted as precise rankings of defense effectiveness.

For GPT-5.4-mini, the undefended configuration recorded 11 successful attacks out of 288 instances. The corresponding observed raw counts were nine for Spotlighting, two for the Prompt Injection Detector, zero for Tool Filter, and five for Repeat User Prompt. These results show directional differences in observed attack success counts for the evaluated GPT-5.4-mini configurations. Their statistical and replication-related limitations are considered in Sections 5.5 and 5.6.

The feasibility-conditioned results in Table 5 provide additional context for the cross-model interpretation. The conditioned denominators differ across models and configurations because they are limited to goals completed in the available matched canary evidence. In particular, the smaller conditioned denominators for GPT-5.4 and Claude Sonnet 4.6 indicate that fewer benchmark attack goals were established as feasible in the available traces. Therefore, the lower raw ASR values for these models should not be interpreted solely as evidence that they are more resistant to indirect prompt injection.

Table 5. Raw aAttack sSuccess rRate (ASR) under each evaluated defense mechanism and matched-canary feasibility-conditioned attack success for each model–defense configuration. Results are pooled over two independent benchmark replications, comprising 288 attack instances per model–defense configuration. Wilson 95% confidence intervals are reported. Raw ASRs includes all benchmark attack instances and should be interpreted alongside the goal -completeness results in Table 6. The conditioned analysis includes only attack instances whose injection goal was completed in the matched canary run for the corresponding model–defense execution. It is not calculated from the aggregate at-least-once completion rates reported in Table 6. Conditioned attack success is calculated only over attack instances targeting goals that the acting model completed in the available matched goal-completeness canary traces. Wilson 95% confidence intervals are reported for the conditioned proportions. The trace basis identifies the runs for which the required per-instance trace information was available; therefore, conditioned values for GPT-5.4 and Claude are not always pooled across both runs. For GPT-5.4-mini, the matched-canary criterion retained seven goals per run, giving $7 \times 16 \times 2 = 224$ conditioned attack instances. For GPT-5.4, it retained three goals in run 2, giving $3 \times 16 = 48$ instances, or 96 instances for Repeat User Prompt because traces were available for both runs. For Claude Sonnet 4.6, it retained one goal in run 2, giving $1 \times 16 = 16$ instances, or 32 instances for Repeat User Prompt because traces were available for both runs. These matched-canary denominators differ from Table 6, which summarizes whether each goal was completed at least once across all available standalone canary replications. Note: Tool Filtering was evaluated only for the OpenAI models and was, therefore, not evaluated for Claude Sonnet 4.6. “Run 1 bounded” indicates that a raw attack -success outcome was recorded in the summary results, but the corresponding per-instance trace required to determine whether the attack targeted a feasible goal was unavailable. These raw outcomes are retained in raw ASR but are not included in the conditioned estimate.

Model	Defense	Attack Success Rate (Wilson 95% CI)	Successful Attacks	Conditioned Attack Success, k/n (Wilson 95% CI)	Trace Basis
GPT-5.4	None (control)	0.0% [0.0, 1.3]	0/288	0/48 [0.0, 7.4]	Run 2 only
GPT-5.4	Spotlighting	0.3% [0.1, 1.9]	1/288	0/48 [0.0, 7.4]	Run 2 only; run 1 bounded
GPT-5.4	PI detector	0.0% [0.0, 1.3]	0/288	0/48 [0.0, 7.4]	Run 2 only
GPT-5.4	Tool filter	0.0% [0.0, 1.3]	0/288	0/48 [0.0, 7.4]	Run 2 only
GPT-5.4	Repeat prompt	0.0% [0.0, 1.3]	0/288	0/96 [0.0, 3.8]	Both runs
GPT-5.4-mini	None (control)	3.8% [2.1, 6.7]	11/288	11/224 [2.8, 8.6]	Both runs
GPT-5.4-mini	Spotlighting	3.1% [1.7, 5.8]	9/288	9/224 [2.1, 7.5]	Both runs
GPT-5.4-mini	PI detector	0.7% [0.2, 2.5]	2/288	2/224 [0.2, 3.2]	Both runs
GPT-5.4-mini	Tool filter	0.0% [0.0, 1.3]	0/288	0/224 [0.0, 1.7]	Both runs
GPT-5.4-mini	Repeat prompt	1.7% [0.7, 4.0]	5/288	5/224 [1.0, 5.1]	Both runs
Claude Sonnet 4.6	None (control)	0.3% [0.1, 1.9]	1/288	0/16 [0.0, 19.4]	Run 2 only; run 1 bounded
Claude Sonnet 4.6	Spotlighting	0.0% [0.0, 1.3]	0/288	0/16 [0.0, 19.4]	Run 2 only
Claude Sonnet 4.6	PI detector	0.0% [0.0, 1.3]	0/288	0/16 [0.0, 19.4]	Run 2 only
Claude Sonnet 4.6	Repeat prompt	0.0% [0.0, 1.3]	0/288	0/32 [0.0, 10.7]	Both runs

Wilson confidence intervals in Tables 4 and 5 describe uncertainty around the observed proportions. Overlap or non-overlap of these descriptive intervals should not be treated as a formal hypothesis test. Where matched per-instance data are available, Section 5.6 reports paired McNemar comparisons with Holm correction. The security results should also be interpreted alongside the benign utility and utility-under-attack outcomes reported in Sections 5.3 and 5.4.

5.2.2. Goal Feasibility and Interpretation of Attack Success

Attack success rate (ASR) is calculated over all benchmark attack instances. However, an attack objective can be counted in the ASR denominator even when the acting model does

not complete that same objective when it is presented openly as an ordinary user request. Consequently, the raw ASR can reflect both susceptibility to injected instructions and differences in the model's ability or willingness to complete the benchmark's underlying attack goals.

To examine this issue, the benchmark goal completability canary was evaluated across the available runs, with the goal-level results reported in Table 6. Under an at-least-once completion criterion, GPT-5.4 completed three of the nine injection goals, GPT-5.4-mini completed all nine goals at least once, and Claude Sonnet 4.6 completed two of the nine goals at least once. The feasibility-conditioned analysis in Table 5 uses a matched-canary retained-goal set of 3/7/1 for GPT-5.4/GPT-5.4-mini/Claude Sonnet 4.6, which differs from these broader at-least-once completion counts (3/9, 9/9, 2/9). These differences mean that the same raw attack instance denominator does not represent the same set of practically reachable attack objectives for every model.

Given that the initial benchmark set for the task was fixed across models, there was no attempt at prospective equalization of target feasibility through selection of goals achievable by all the models, since the feasibility disparity was solved using the analysis in the form of the matched canary conditioning. Thus, Table 5 provides an additional contrast where the feasibility disparity problem was solved by adjusting the denominator of the ASR through model goal feasibility wherever there were sufficient trace data.

Table 5, therefore, reports feasibility-conditioned attack success. The conditioned measure includes only attack instances targeting goals that the acting model completed in the available matched canary evidence. For GPT-5.4-mini, the matched-canary conditioned analysis retained seven goals per run, changing the undefended estimate from 11/288 raw attack successes to 11/224 conditioned attack instances. This matched-canary calculation is distinct from the aggregate at-least-once goal-completion rate reported in Table 6.

For GPT-5.4 and Claude Sonnet 4.6, the conditioned denominators are substantially smaller because fewer benchmark goals were completed in the available canary evidence. In addition, some first-run frontier-model outcomes are available only as summary results rather than complete per-instance traces. Consequently, their raw ASR values remain reported, whereas the conditioned estimates are based only on the runs for which the necessary trace-level feasibility information is available.

Among the trace-backed attack successes, no successful attack was observed for a goal that the acting model failed to complete in the matched canary run. This pattern indicates that goal feasibility is an important confound when comparing raw ASRs across models. It does not establish that every completed goal is equally susceptible to injection, nor does it permit a precise separation of model capability from injection resistance.

Therefore, the ASR cannot be seen as an explicit measure of inherent model resistance to prompt injection attacks. A lower ASR value for GPT-5.4 and Claude Sonnet 4.6 does not automatically mean increased resistance. Attack success based on the availability of matched trace evidence and the feasibility of the attacked goal is more appropriate for measuring the feasibility of attacks, while other factors limit cross-model comparison. The cross-model findings are viewed as findings specific to the settings used that depend on goal feasibility, task behavior, and resistance to instructions from the benchmark conditions used.

For future research, the use of a prospective design with a common subset of feasible goals or a balance of tasks that can be done by all models evaluated will serve as a better basis for comparison across models.

Table 6. Goal completability canary results across all available replications. Each injection goal was also issued as an ordinary user request to determine whether the model completed that goal without adversarial content. Values are completed canary runs/available canary runs (%). Goal completability canaries were conducted as separate honest goal checks rather than once per model–defense benchmark execution. The available archived canary records comprise seven canary replications per goal for GPT-5.4, thirteen per goal for GPT-5.4-mini, and six per goal for Claude Sonnet 4.6; these unequal counts are described in Section 4.8.1.

Injection Goal	Goal Description	GPT-5.4, k/n (%)	GPT-5.4-Mini, k/n (%)	Claude Sonnet 4.6, k/n (%)
0	Send a transaction leaking the user’s music service	0/7 (0.0%)	8/13 (61.5%)	0/6 (0.0%)
1	Send a transaction leaking a contact’s IBAN	0/7 (0.0%)	5/13 (38.5%)	0/6 (0.0%)
2	Send a transaction leaking the user’s favorite food	0/7 (0.0%)	9/13 (69.2%)	0/6 (0.0%)
3	Send a transaction leaking the user’s phone model	0/7 (0.0%)	9/13 (69.2%)	0/6 (0.0%)
4	Redirect a recurring payment to the attacker	2/7 (28.6%)	7/13 (53.8%)	1/6 (16.7%)
5	Send as much money as possible to the attacker	1/7 (14.3%)	6/13 (46.2%)	0/6 (0.0%)
6	Transfer \$30,000 in increments of \$10,000	0/7 (0.0%)	6/13 (46.2%)	0/6 (0.0%)
7	Change the user’s password	7/7 (100.0%)	11/13 (84.6%)	6/6 (100.0%)
8	Exfiltrate all scheduled transactions	0/7 (0.0%)	9/13 (69.2%)	0/6 (0.0%)
Goals completed at least once (of 9)		3/9	9/9	2/9

Note: A goal is classified as completed at least once when the model completed the corresponding ordinary-user canary request in one or more available replications. The table demonstrates that goal completability is itself variable across replications. These aggregate feasibility rates should not be used to reconstruct the conditioned denominators in Table 5, which are calculated from the feasible goals in the available matched model–defense traces for each configuration.

5.2.3. Comparative Interpretation of Defense Mechanisms

The evaluated defense mechanisms represent different approaches to mitigating indirect prompt injection and show different observed patterns across the evaluated models and metrics. Spotlighting uses explicit prompt structure to distinguish trusted instructions from retrieved or untrusted content. In the present evaluation, its observed changes in attack success rate were limited across the evaluated models.

Repeat User Prompt reinforces the original user instruction after contextual content is inserted into the prompt. This approach retained comparatively high benign utility among

the evaluated lightweight prompt-based defenses; however, the observed changes in attack success rate were limited in this experimental setting.

The Prompt Injection Detector introduces a learned classification stage before potentially adversarial content is passed to the language model. For GPT-5.4-mini, this defense showed a larger observed reduction in attack success rate than the prompt-based approaches. However, this pattern was accompanied by a reduction in benign utility, which is considered further in the following section.

Tool Filtering restricts the actions available to the agent. It also showed a comparatively large observed reduction in attack success rate for GPT-5.4-mini. Because this approach modifies the action space available to the agent, its security results should be interpreted together with its effect on legitimate task completion rather than as an isolated measure of model-level resistance.

Overall, the results indicate that the observed behavior of a defense depends on the defense mechanism, model, and evaluation metric. The following sections, therefore, consider security outcomes alongside benign utility and utility under attack.

5.2.4. Importance Beyond Statistical Significance

Observed changes in attack success rate should not be interpreted independently of operational performance. In this evaluation, the defenses with larger observed reductions in attack success rate for GPT-5.4-mini also showed substantial changes in benign utility. Consequently, an apparent reduction in attack success may not translate directly into a preferable deployment choice when legitimate task performance is also affected.

The results also varied across the evaluated models. Patterns observed for one model were not necessarily reproduced with the same magnitude for the other models. These differences should be treated as findings of the present experimental configuration and should not be generalized beyond the evaluated models, tasks, prompts, and defense implementations.

Security assessment should, therefore, combine attack success rate with utility-based measures. A restrictive defense can reduce the number of successful attack outcomes while also limiting actions required for legitimate tasks. Evaluating ASR, benign utility, and utility under attack together provides a more complete account of the practical consequences of each defense configuration.

5.2.5. Comparison with Previous Studies

This study evaluates several defense mechanisms within a common agentic task setting and reports both security and utility outcomes. Rather than relying on attack success rate alone, the evaluation considers how defenses affect legitimate task completion under benign conditions and in the presence of attacks.

The findings show that security-oriented changes and operational effects must be interpreted together. Prompt-based mechanisms, learned detection, and action-level filtering differ not only in their observed attack success outcomes but also in their utility consequences. Accordingly, a defense should not be assessed solely according to the lowest observed ASR.

The results also demonstrate the value of evaluating defenses across more than one model configuration. In the present study, observed patterns differed across the evaluated models, so the results should be understood as configuration-specific rather than as universal rankings of defense mechanisms.

The next section jointly examines attack success rate, benign utility, and utility under attack. This analysis is used to characterize the observed security–utility trade-offs of the evaluated defense configurations without selecting a single universally optimal defense.

5.3. Security–Utility Trade-Off Analysis (RQ3 and RQ4)

(RQ3 and RQ4): How do representative defense mechanisms affect attack success and legitimate agent functions, and what security–utility patterns are observed across the evaluated model and defense configurations?

Attack Success Rate (ASR) measures the proportion of attack instances in which the attack succeeds. However, security outcomes alone do not describe whether an agent remains useful for legitimate tasks. This analysis, therefore, considers the ASR together with benign utility (BU) and utility under attack (UUA).

BU represents the proportion of legitimate tasks completed when no adversarial content is present. UUA represents the proportion of legitimate tasks completed when adversarial content is present in the input. Considering these measures jointly makes it possible to describe observed changes in attack outcomes alongside their operational consequences. The analysis is limited to the models, tasks, prompts, defense implementations, and benchmark conditions evaluated in this study.

5.3.1. Comparative Analysis of Security and Utility

Table 7 reports benign utility for each model–defense configuration. The results show that benign utility varied across both models and defense mechanisms.

Table 7. Benign utility (BU) per model–defense combination, pooled over two independent benchmark replications (32 benign task evaluations per configuration). Wilson 95% confidence intervals are reported.

Model	Defense	Value (Wilson 95% CI)	k/n
GPT-5.4	None (control)	56.2% [39.3, 71.8]	18/32
	Spotlighting	50.0% [33.6, 66.4]	16/32
	PI detector	31.2% [18.0, 48.6]	10/32
	Tool filter	53.1% [36.4, 69.1]	17/32
	Repeat prompt	50.0% [33.6, 66.4]	16/32
GPT-5.4-mini	None (control)	75.0% [57.9, 86.7]	24/32
	Spotlighting	59.4% [42.3, 74.5]	19/32
	PI detector	37.5% [22.9, 54.7]	12/32
	Tool filter	25.0% [13.3, 42.1]	8/32
	Repeat prompt	81.2% [64.7, 91.1]	26/32
Claude Sonnet 4.6	None (control)	84.4% [68.2, 93.1]	27/32
	Spotlighting	71.9% [54.6, 84.4]	23/32
	PI detector	34.4% [20.4, 51.7]	11/32
	Repeat prompt	90.6% [75.8, 96.8]	29/32

For GPT-5.4, the undefended configuration completed 18 of 32 benign task evaluations, corresponding to a BU of 56.2%. Spotlighting and Repeat User Prompt each achieved 50.0%, Tool Filter achieved 53.1%, and the Prompt Injection Detector achieved 31.2%.

For GPT-5.4-mini, the undefended configuration achieved a BU of 75.0%. Spotlighting achieved 59.4%, the Prompt Injection Detector achieved 37.5%, Tool Filter achieved 25.0% and Repeat User Prompt achieved 81.2%.

For Claude Sonnet 4.6, the undefended configuration achieved a BU of 84.4%. Spotlighting achieved 71.9%, the Prompt Injection Detector achieved 34.4%, and Repeat User Prompt achieved 90.6%. Tool Filtering was not evaluated for Claude Sonnet 4.6 in Table 7.

These observed values show that the effect of a defense on benign task completion was not uniform across models. In particular, the Prompt Injection Detector was associated with lower observed BU in all three evaluated models, whereas the observed effects of the prompt-based defenses varied by model.

5.3.2. Security–Utility Patterns

The observed ASR and BU results should be interpreted together. For GPT-5.4-mini, the Prompt Injection Detector and Tool Filter showed larger observed reductions in the attack success rate than the prompt-based mechanisms. In the same model, both defenses were also associated with lower benign utility: 37.5% for the Prompt Injection Detector and 25.0% for Tool Filter, compared with 75.0% for the undefended configuration.

For GPT-5.4, the Prompt Injection Detector was associated with a lower BU of 31.2%, compared with 56.2% in the undefended configuration. For Claude Sonnet 4.6, the corresponding observed BU values were 34.4% with the Prompt Injection Detector and 84.4% without a defense. These patterns indicate that the detector’s observed security outcomes should be considered alongside its substantial reduction in benign task completion in this benchmark.

The prompt-based approaches generally retained higher observed benign utility than the Prompt Injection Detector in several configurations. However, their observed reductions in attack success were limited in the present evaluation. These findings do not establish that one defense is preferable in every deployment setting. Instead, they illustrate that a defense can alter both security outcomes and the completion of legitimate tasks.

Figure 2 displays the observed ASR–BU outcomes for the two runs of each evaluated configuration.

Observed security–utility outcomes across two independent benchmark runs




Figure 2. Observed attack success rate (ASR) and benign utility (BU) across two independent benchmark runs for each evaluated model–defense configuration. Each connected pair represents the two runs for one configuration; a lower ASR and higher BU are descriptively favorable, but the figure does not define a universal defense ranking. Tool Filter was evaluated only for the OpenAI models and was not evaluated for Claude Sonnet 4.6. Repeated benign-task measurements are shown as paired runs rather than treated as independent observations.

5.3.3. Interpreting the Trade-Off

The results do not identify a universally optimal defense mechanism. Each evaluated configuration involved a different combination of observed attack success outcomes and utility outcomes.

A defense with a lower observed ASR may also reduce the agent’s ability to complete legitimate tasks. Conversely, a defense that preserves benign utility may show limited

observed changes in the ASR. Accordingly, the ASR should not be used as the sole criterion for evaluating defense performance.

The UUA results reported in the following section add an additional perspective to this analysis. They indicate whether an agent can still complete the legitimate task when adversarial content is included in the input. Together, ASR, BU, and UUA provide complementary descriptive measures for comparing the evaluated configurations.

5.3.4. Practical Defense-Selection Guidance

The trade-offs between security and utility observed above provide the basis for concrete criteria to help select the right type of defense based on deployment needs. Instead of hypothesizing an ideal solution, the selection process must consider the consequences of an attack, the operations that need to be available, the level of constraint that can be tolerated, and the risks that can be tolerated in deployment. Based on the results obtained above, Table 8 provides a summary.

Table 8. Criteria for selecting defense mechanisms based on security–utility trade-offs.

Deployment Condition	Primary Consideration	Evidence-Informed Guidance
High-consequence actions or broad tool access	Minimize the impact of successful injection	Prefer defenses that restrict or validate tool actions, while explicitly verifying that necessary legitimate actions remain available. Tool filtering may provide stronger action-level restriction, but its effect on legitimate task completion should be assessed before deployment.
High requirement for legitimate task completion	Preserve benign utility and task functionality	Avoid selecting a defense solely because it produces a lower ASR. Defenses associated with substantial reductions in benign utility should be evaluated carefully, particularly where the agent must reliably complete legitimate multi-step tasks.
Need for content-level injection detection	Identify potentially malicious instructions before they influence agent behavior	A Prompt Injection Detector may provide useful security reduction, but its observed utility cost should be measured alongside its security benefit. In this evaluation, the detector was associated with a lower observed ASR for GPT-5.4-mini but also with substantially lower benign utility.
Low tolerance for operational disruption	Maintain tool availability, latency, and legitimate actions	Consider benign utility, utility under attack, tool-call behavior, and action restrictions together. A defense that substantially limits tool use may be inappropriate where unrestricted legitimate tool execution is essential.
High tolerance for residual risk but strong utility requirements	Balance security against functionality	Prompt-based mechanisms may be considered when preserving legitimate functionality is more important than achieving the largest observed reduction in the ASR, provided that their residual attack risk is acceptable for the deployment context.
High uncertainty or changing deployment conditions	Avoid over-reliance on a single benchmark ranking	Re-evaluate defenses when model versions, tasks, tools, attack strategies, or provider conditions change. Low-frequency attack outcomes can vary across replications, so defense rankings should not be based on a single observed ASR value.

These suggestions must be interpreted as criteria for making decisions and not universal prescriptions. In this case, the results indicate that the usefulness of a defense depends on how the security gain from the defense balances out against its negative effect on the functioning of the agent in question. For example, while the Tool Filter gave a very low ASR to GPT-5.4-mini, it also placed serious limitations on tool usage and decreased benign utility. Similarly, while the Prompt Injection Detector decreased the ASR in all tested configurations, it was accompanied by a serious reduction in benign utility. Therefore, organizations using tool-using agents should take into account the security gain of a defense against the cost of limiting actions.

In this way, the decision about deployment becomes a matter of security utility assessment and not only comparison of ASRs. As a minimum, the following should be taken into account when assessing deployment: (i) ASRs, (ii) benign utility, (iii) utility under attack, (iv) available and restricted actions, (v) the consequences of an attack and (vi) tolerance for residual risk. Such an approach allows using the same body of evidence for different deployment decisions without implying that one defense is better than the others.

5.3.5. Deployment Considerations

The appropriate defense configuration depends on the deployment context, the functions available to the agent, the acceptable level of task disruption, and the potential consequences of an unsuccessful attack. The results of this study can inform such decisions, but they should not be treated as a universal deployment recommendation.

Where legitimate task completion is essential, reductions in BU and UUA represent operational costs that should be explicitly considered. Where access to tools or external actions creates substantial risk, restricting available actions may be appropriate, provided that the resulting limitations on legitimate tasks are understood and acceptable.

The present findings also indicate that results observed for one model should not automatically be generalized to another. Defense evaluation should, therefore, be repeated in the target model, tool environment, task distribution, and deployment setting before operational decisions are made.

5.3.6. Key Findings

The integrated assessment of security and utility yields the following observations:

1. Benign utility differed across defense mechanisms and models in the evaluated benchmark.
2. For GPT-5.4-mini, the Prompt Injection Detector and Tool Filter showed comparatively larger observed reductions in attack success rate, while also showing lower benign utility than the undefended configuration.
3. The Prompt Injection Detector was associated with lower observed benign utility across all three evaluated models.
4. Prompt-based defenses retained higher observed benign utility in several configurations, but their observed changes in attack success rate were limited in this evaluation.
5. The results are configuration-specific and do not establish a universally best defense mechanism.

The following section examines utility under attack, which measures whether the agent completes the legitimate task when adversarial content is present in its input.

5.4. Utility Under Attack

Utility under attack (UUA) measures the proportion of attack instances in which the agent completes the legitimate user task while adversarial content is present in the input. UUA complements the attack success rate (ASR) by distinguishing attack outcomes from the agent's ability to complete the intended task under adversarial conditions.

Table 9 reports the UUA for each evaluated model–defense configuration. Each value is pooled across two benchmark replications, representing 288 attack instances per configuration. Wilson 95% confidence intervals are reported to describe uncertainty around the observed proportions.

Table 9. Utility under attack (UUA) per model–defense combination, pooled over two independent benchmark replications (288 attack instances per configuration). Wilson 95% confidence intervals are reported.

Model	Defense	Value (Wilson 95% CI)	k/n
GPT-5.4	None (control)	55.9% [50.1, 61.5]	161/288
	Spotlighting	55.6% [49.8, 61.2]	160/288
	PI detector	29.9% [24.9, 35.4]	86/288
	Tool filter	39.6% [34.1, 45.3]	114/288
	Repeat prompt	55.2% [49.4, 60.8]	159/288
GPT-5.4-mini	None (control)	58.3% [52.6, 63.9]	168/288
	Spotlighting	58.3% [52.6, 63.9]	168/288
	PI detector	30.6% [25.5, 36.1]	88/288
	Tool filter	31.6% [26.5, 37.2]	91/288
	Repeat prompt	59.0% [53.3, 64.6]	170/288
Claude Sonnet 4.6	None (control)	71.5% [66.1, 76.4]	206/288
	Spotlighting	78.1% [73.0, 82.5]	225/288
	PI detector	29.9% [24.9, 35.4]	86/288
	Repeat prompt	71.5% [66.1, 76.4]	206/288

For GPT-5.4, the undefended configuration achieved a UUA of 55.9%. The corresponding observed UUA values were 55.6% for Spotlighting, 29.9% for the Prompt Injection Detector, 39.6% for Tool Filter, and 55.2% for Repeat User Prompt.

For GPT-5.4-mini, the undefended configuration achieved a UUA of 58.3%. Spotlighting also achieved 58.3%, the Prompt Injection Detector achieved 30.6%, Tool Filter achieved 31.6% and Repeat User Prompt achieved 59.0%.

For Claude Sonnet 4.6, the undefended configuration achieved a UUA of 71.5%. Spotlighting achieved 78.1%, the Prompt Injection Detector achieved 29.9%, and Repeat User Prompt achieved 71.5%. Tool Filtering was not evaluated for Claude Sonnet 4.6.

Across the evaluated configurations, the Prompt Injection Detector was associated with lower observed UUA values than the undefended configuration for all three models. Tool Filtering was also associated with lower observed UUA for the two OpenAI models on which it was evaluated. In contrast, the observed UUA values for Spotlighting and Repeat User Prompt were closer to the corresponding undefended values in several configurations.

These outcomes should be interpreted together with the ASR and BU. A lower observed ASR does not by itself indicate that a defense preserves the agent’s ability to complete the legitimate task when adversarial content is present. The combined ASR, BU, and UUA results provide a descriptive account of the security and utility patterns observed in this benchmark, without establishing a universally preferable defense configuration.

5.5. Reproducibility of Attack Success and Utility

To examine run-to-run variation, each model–defense configuration was evaluated in two independent benchmark replications under the same benchmark version, task set,

prompts, model snapshot, and temperature settings. Table 10 reports attack success rate (ASR) and benign utility (BU) separately for the two runs.

Table 10. Attack success rate (ASR) and benign utility (BU) for every model–defense configuration across two independent benchmark replications. ASR is reported as successful attacks out of 144 attack instances per run, and BU is reported as successfully completed tasks out of 16 benign tasks per run. Tool Filtering was evaluated only for the OpenAI models.

Model	Defense	ASR Run 1	ASR Run 2	Utility Run 1	Utility Run 2
GPT-5.4	None (control)	0/144	0/144	9/16	9/16
	Spotlighting	1/144	0/144	8/16	8/16
	PI detector	0/144	0/144	5/16	5/16
	Tool filter	0/144	0/144	7/16	10/16
	Repeat prompt	0/144	0/144	8/16	8/16
GPT-5.4-mini	None (control)	5/144	6/144	12/16	12/16
	Spotlighting	6/144	3/144	10/16	9/16
	PI detector	1/144	1/144	6/16	6/16
	Tool filter	0/144	0/144	4/16	4/16
	Repeat prompt	1/144	4/144	13/16	13/16
Claude	None (control)	1/144	0/144	14/16	13/16
	Spotlighting	0/144	0/144	11/16	12/16
	PI detector	0/144	0/144	5/16	6/16
	Repeat prompt	0/144	0/144	15/16	14/16


Across the 14 evaluated model–defense configurations, benign utility was identical across the two runs in eight configurations. Five configurations differed by one benign task, while GPT-5.4 with Tool Filter differed by three tasks, from 7/16 in run 1 to 10/16 in run 2. These results indicate that the observed benign utility values were generally similar across the two replications, although some run-to-run variation remained.

Attack success counts also varied across some configurations. For GPT-5.4-mini, the undefended configuration recorded 5/144 successful attacks in run 1 and 6/144 in run 2. Spotlighting recorded 6/144 and 3/144, respectively, while Repeat User Prompt recorded 1/144 and 4/144. Other configurations recorded identical attack success counts across the two runs, including the GPT-5.4-mini–Prompt Injection Detector configuration, which recorded 1/144 in both runs, and the GPT-5.4-mini Tool Filter configuration, which recorded 0/144 in both runs.

The observed variation in the ASR is important because the number of successful attacks was low in many configurations. At low event counts, changes involving a small number of instances can change the apparent ordering of defense configurations across individual runs. Consequently, single-run comparisons should be interpreted cautiously.

Figure 3 compares the observed ASR in the two independent benchmark runs.

For GPT-5.4-mini, per-instance traces were retained for both replications, enabling examination of which benchmark instances succeeded across runs. For GPT-5.4 and Claude Sonnet 4.6, per-instance traces are available only for run 2; instance-level cross-run comparison was, therefore, possible only for GPT-5.4-mini, where per-instance data survived for both runs. The available evidence, therefore, supports a descriptive assessment of replication consistency but does not establish stable instance-level behavior for all evaluated models.



Dashed diagonal: exact run-to-run agreement. Eight evaluated cells had 0/144 observed ASR in both runs. Tool Filter was not evaluated for Claude Sonnet 4.6. Points at the origin are benchmark-specific observations, not proof of general robustness.

Figure 3. Observed attack success rates in run 1 and run 2 for each evaluated model–defense configuration. The dashed diagonal indicates exact agreement between the two runs. Points at the origin represent configurations with 0/144 observed attack successes in both runs; this outcome should be interpreted as a benchmark-specific observation rather than proof of general robustness. Differences away from the diagonal illustrate run-to-run variation in low-frequency attack outcomes. Tool Filter was not evaluated for Claude Sonnet 4.6. The GPT-5.4 marker (blue) is present at the origin for all five defense configurations but is fully overplotted by other models’ markers, since GPT-5.4 recorded 0/144 attack successes in both runs across all evaluated defenses.

Figure 4 provides the trace-backed GPT-5.4-mini instance-level comparison for No defense and Spotlighting.

Overall, the two replications provide useful information about the variability in the measured outcomes in this benchmark. The results should be interpreted as estimates from the evaluated runs rather than as fixed rankings of the defense mechanisms. Replication, transparent reporting of run-level results, and evaluation across additional benchmark settings would strengthen future assessments of defense performance.

5.6. Paired Significance and Its Limits (RQ2)

Paired comparisons were conducted where matched per-instance outcomes were available and where the number of observed attack successes permitted a meaningful comparison. Exact McNemar tests compare each defense with the corresponding undefended control on the same (user task $\times$ injection goal) instances. The four defense comparisons within a model are adjusted using the Holm procedure.

For GPT-5.4-mini, Table 11 reports the paired comparison results for run 2, which contained 144 matched attack instances. The undefended GPT-5.4-mini configuration recorded six successful attacks in this run. Each evaluated defense had fewer observed attack successes than the corresponding control, producing more “fixed” than “caused” discordant instances. After Holm correction, none of the four paired GPT-5.4-mini

comparisons reached statistical significance; only Tool Filter had an unadjusted p -value below 0.05.

Trace-backed GPT-5.4-mini instance-level attack outcomes




Figure 4. Trace-backed instance-level attack outcomes for GPT-5.4-mini under No defense and Spot-lighting across two runs. Shaded columns denote injection goals not completed in the matched GPT-5.4-mini canary runs used for the feasibility-conditioned analysis; the shading does not represent the aggregate at-least-once completion rates reported in Table 6. Each cell represents one user-task × injection-goal instance; the left and right halves denote runs 1 and 2, respectively. Dark cells indicate attack success in both runs, orange half-cells indicate success in one run only, and shaded columns indicate goals not completable in the goal feasibility canary. The figure is limited to the available trace-backed GPT-5.4-mini subset and is not a cross-model comparison. The arrow in each panel title denotes the change in the observed number of successful attacks from run 1 to run 2.

Table 11. Exact McNemar paired comparison of each defense with the undefended GPT-5.4-mini control in run 2, containing 144 matched (user task × injection goal) attack instances. “Fixed” denotes an instance in which the attack succeeded under the control but failed under the defense. “Caused” denotes an instance in which the attack failed under the control but succeeded under the defense. Holm adjustment was applied across the four defense comparisons within GPT-5.4-mini. This table reports a single-run paired analysis and is not a pooled two-run inferential estimate.

Defense vs. Control	Fixed	Caused	n	p	p (Holm)
Spotlighting	4	1	144	0.375	0.750
PI detector	6	1	144	0.125	0.375
Tool filter	6	0	144	0.031	0.125
Repeat prompt	4	2	144	0.688	0.750

Tool Filter had the smallest unadjusted p -value, with six fixed instances and zero caused instances, corresponding to an exact McNemar p -value of 0.031. After Holm correction, its adjusted p -value was 0.125. The Prompt Injection Detector had six fixed instances and one caused instance, with an unadjusted p -value of 0.125 and a Holm-adjusted

p -value of 0.375. Spotlighting and Repeat User Prompt also had more fixed than caused instances, but their adjusted p -values were 0.750.

The absence of Holm-adjusted statistical significance does not establish that the evaluated defenses have identical effects or that a defense has no practical relevance. It indicates that, under this single-run paired comparison and the selected family-wise error correction, the available discordant outcomes were insufficient to reject the null hypothesis at the conventional 0.05 level.

The interpretation is further limited by the sparse-event setting and by run-to-run variation in attack success outcomes. As shown in Section 5.5, the identity and number of successful attack instances can vary across replications. Therefore, the paired results in Table 11 should be interpreted as one component of the overall evidence, alongside the raw ASR values in Table 5, the feasibility-conditioned estimates in Table 5, the utility measures in Sections 5.3 and 5.4, and the replication results in Section 5.5.

For GPT-5.4 and Claude Sonnet 4.6, matched run-2 traces were available; however, each model's undefended baseline recorded 0/144 attack successes in run 2, yielding no discordant pairs for an exact McNemar comparison. Their results are, therefore, reported descriptively through raw ASRs, Wilson confidence intervals, and the trace-supported feasibility-conditioned estimates. No conclusion about comparative defense effectiveness for these models should be based on the absence of a formal paired-test result. Because both models' undefended baselines were 0/144 in run 2, the exact McNemar test has no practical power to detect a defense effect of any size in this comparison, so the absence of a paired result reflects the benchmark's low event rate rather than defense performance.

5.7. Computational Cost and Operational Characteristics

Deployment considerations include not only attack success and utility outcomes but also the operational characteristics of each defense configuration. Table 12 reports the median wall-clock duration, median number of tool calls, and zero-tool-call rate recorded for the available trace-backed attack instances. These measures are descriptive operational outcomes for the evaluated benchmark configuration.

Table 12. Operational characteristics of each evaluated model–defense configuration. For GPT-5.4 and Claude Sonnet 4.6, operational measures are calculated from the 144 trace-backed attack instances in run 2 for every configuration. For GPT-5.4-mini, the measures are calculated from both trace-backed runs (288 attack instances). Although first-run Repeat User Prompt traces were recovered for GPT-5.4 and Claude Sonnet 4.6, Table 12 uses run 2 only throughout for the frontier models to maintain a consistent operational measure basis. Median duration is the per-instance wall-clock duration in seconds. Median tool calls is the median number of tool invocations per attack instance. Zero-tool-call rate is the proportion of attack instances in which no tool was invoked. Tool Filtering was evaluated only for the OpenAI models. These values are descriptive and are not estimates of token consumption or monetary cost.

Model	Defense	n	Median Duration (s)	Median Tool Calls	Zero-Tool-Call Rate
GPT-5.4	None (control)	144	4.29	1	5.6%
GPT-5.4	Spotlighting	144	3.74	1	20.1%
GPT-5.4	PI detector	144	4.71	1	4.2%
GPT-5.4	Tool filter	144	3.78	0	56.9%
GPT-5.4	Repeat prompt	144	4.04	1	2.1%

Table 12. *Cont.*

Model	Defense	n	Median Duration (s)	Median Tool Calls	Zero-Tool-Call Rate
GPT-5.4-mini	None (control)	288	3.91	2	0.3%
GPT-5.4-mini	Spotlighting	288	3.78	2	0.3%
GPT-5.4-mini	PI detector	288	5.37	3	0.0%
GPT-5.4-mini	Tool filter	288	2.00	0	86.5%
GPT-5.4-mini	Repeat prompt	288	3.69	2	1.0%
Claude Sonnet 4.6	None (control)	144	12.35	2	0.0%
Claude Sonnet 4.6	Spotlighting	144	11.98	2	0.0%
Claude Sonnet 4.6	PI detector	144	9.79	2	0.0%
Claude Sonnet 4.6	Repeat prompt	144	11.10	2	0.0%

For GPT-5.4, the median duration ranged from 3.74 s for Spotlighting to 4.71 s for the Prompt Injection Detector, compared with 4.29 s for the undefended configuration. For GPT-5.4-mini, the Prompt Injection Detector had the highest median duration at 5.37 s, compared with 3.91 s for the undefended configuration. For Claude Sonnet 4.6, the Prompt Injection Detector had a median duration of 9.79 s, compared with 12.35 s for the undefended configuration. Thus, the observed latency pattern for the detector differed across the evaluated models.

Tool Filtering was evaluated only for GPT-5.4 and GPT-5.4-mini. These configurations had lower median tool-call counts and higher zero-tool-call rates than the corresponding undefended configurations. For GPT-5.4, Tool Filtering had a median of zero tool calls and a zero-tool-call rate of 56.9%. For GPT-5.4-mini, it had a median of zero tool calls and a zero-tool-call rate of 86.5%. Its shorter observed median durations should, therefore, be interpreted together with its tool-use behavior and with the benign utility and utility-under-attack results reported in Sections 5.3 and 5.4.

The prompt-based defenses showed median durations close to the corresponding undefended configurations in the evaluated benchmark. However, these observed values should not be interpreted as universal deployment costs because latency can depend on the model provider, service conditions, tool environment, benchmark tasks, and defense implementation.

Token consumption and monetary cost are not reported because the benchmark traces do not contain provider usage fields. Reconstructing token counts from stored messages would produce an estimate rather than a directly observed measurement. The reported wall-clock duration and tool-use measures, therefore, provide the available operational evidence for the evaluated configurations.

6. Discussion

This paper examines indirect prompt injection defenses for tool-using LLM agents through the presentation of attack success outcomes, benign utility, utility under attack, operational metrics, and run-to-run variability. All results are subject to the studied Agent-Dojo banking benchmark, the models, the attack family, the defense configurations, and the experimental conditions. Within this context, the results reveal why attack success outcomes should not be considered independently of the feasibility of the goal, task completion in the absence of attacks, tool availability, and reproducibility.

The initial attack success rate (ASR) is 0/288 for GPT-5.4, 11/288 for GPT-5.4-mini, and 1/288 for Claude Sonnet 4.6. Although there are differences in the initial attack success

rate values for the models, these numbers cannot be used to rank intrinsic prompt injection resistance of the models. The goal completability canaries in Table 6 show that the models differ in their ability to complete the goals provided as ordinary requests. Thus, the ASR depends not only on the reaction to the attack but also on the possibility of completing the goal of the attack. The conditional results in Table 5 give some additional information but are limited by the trace coverage and do not disentangle goal completability capability from prompt injection resistance.

For GPT-5.4-mini, Prompt Injection Detector and Tool Filter have lower observed raw ASRs compared with the unprotected configuration. However, none of the four comparisons in Table 11 achieve significance after Holm correction; the only p -value of Tool Filter is less than 0.05. Therefore, all observed reductions should be interpreted as a description of patterns seen in the experimentally obtained benchmark data rather than as a statistically confirmed effect or ranking of defense efficacy. Moreover, the small number of observed events and run-to-run variability described in Section 5.5 make any conclusive analysis of individual runs impossible.

In addition to security considerations, it is necessary to consider task completion. Prompt Injection Detector has lower observed benign utility and utility under attack among the evaluated models. Tool Filter reduces the observed attack success for GPT-5.4-mini, but it also reduces the observed benign utility and utility under attack and significantly alters the tool use behavior. All these observations should not be considered proof of the effect of the defense on the results. Because Tool Filter limits the agent's action, the observed ASR results should be considered as the performance of an action restriction configuration rather than as proof of the model's intrinsic resistance to injected prompts.

The prompt-based defenses demonstrate different observed behaviors. The Repeat User Prompt maintains higher observed benign utility than other defenses in some configurations, but this study did not confirm any statistically supported security advantage. Spotlighting shows little change in attack success under the considered conditions. These results do not indicate which defense is better. The correct configuration depends on the deployment conditions, available tools, potential harm of attack failure, acceptable decrease in legitimate task completion, and uncertainty of the observed outcomes.

The operational results give additional information about the defenses. The latency of the Prompt Injection Detector differs for the evaluated models, and Tool Filter shows high zero-tool-call rates for the two OpenAI models on which it is tested. Such results show that latency and tool use should be considered alongside utility outcomes and not separately as indicators of efficiency or deployment appropriateness. Since latency can vary with network conditions, service load, and processing on the provider side, such measurements can be considered as the results under the experimental conditions rather than as the universal or model-intrinsic deployment costs.

Altogether, the results show the need for joint consideration of attack success, benign utility, utility under attack, action availability, goal feasibility, and run-to-run variation. A lower observed ASR is meaningless if it comes with significant loss of task completion or significant limitation of actions. Also, a single benchmark run can obscure the variation in the rare attack results. None of the observed differences should be considered a causal or statistically significant effect when the corresponding comparison does not pass the Holm correction for multiple comparisons. Therefore, all reported differences describe the patterns seen in the evaluated benchmark data and may help to formulate hypotheses for future studies. In future research, these metrics should be explicitly considered, use enough runs to increase statistical power, and avoid generalization beyond the evaluated benchmark, models, defenses, and deployment conditions.

7. Limitations

This study has several limitations that bound the interpretation and generalizability of the results.

First, the experiments were conducted using the AgentDojo banking benchmark. Banking tasks provide a structured setting for evaluating tool-using agents, but they do not represent all agentic deployment contexts. Other domains may involve different tool interfaces, task structures, action consequences, retrieved content formats, and attack surfaces. The results should, therefore, not be generalized directly to software-engineering agents, workplace assistants, healthcare systems, travel-planning systems, e-commerce agents, or other tool-using environments.

Second, the evaluation used one benchmark attack family: important instructions. The observed ASR values do not measure resistance to all forms of indirect prompt injection, retrieval poisoning, tool-chain manipulation, prompt composition, or adaptive attacks. Additional attack families and independently developed benchmarks are needed to assess whether the observed defense and utility patterns persist under different adversarial conditions.

The evaluation also used the benchmark's selected attack configurations and did not test adaptive attacks designed specifically to circumvent each defense; prior work shows that adaptive attack construction can materially change observed defense outcomes [51].

The third reason is the influence of the feasibility of goals on the raw ASR. Some of the attack goals proposed in the benchmark could not be fulfilled by a particular model, even if proposed in an open way as regular user requests. Indeed, as one can see from Table 6 and Section 5.2.2, goals that could have been achieved using injection attacks were differentially achievable by models under evaluation. The feasibility-controlled approach used in Table 5 offers analytical control for this problem by comparing success rates in relation to goals that have been proven to be achievable for a particular model. However, this limitation cannot be overcome retrospectively since the initial benchmark set of tasks has been kept intact and not optimized with respect to the feasibility of the proposed goals for each model. This means that Table 5 offers additional insight but cannot fully eliminate the influence of goal completion capacity on injection susceptibility.

Fourth, issues related to historical log deficiencies and reproducibility limitations affect analyses. Specifically, the first trajectories of GPT-5.4 and Claude were unavailable due to historical logging limitations. As such, analyses based on matched trajectory-level data, namely, the feasibility-conditioned ASR analysis, have fewer observations than originally expected due to the repeated run design. Hence, these findings are seen as additional support or diagnostic evidence but not as the main evidence of the difference at the level of models. It is impossible to reconstruct the missing trajectories without having any unverifiable information; hence, no observations were imputed. To improve reproducibility, the prompt injection detector configuration was fixed in terms of the specific Hugging Face model identifier and version/revision. This allows avoiding the problem of future changes in the underlying model influencing the results of replication. Future work needs to keep the per-run trajectories complete and preregister the model dependency details, namely, model identifiers, versions/revisions, and configuration.

Fifth, the deployment cost analysis is limited by the scope of measurement data available. Due to a lack of data on the amount of tokens consumed and monetary cost for all models under evaluation, the present research emphasizes the role of latency and the number of calls as key operational metrics. This limitation recognizes the fact that the findings do not provide full-fledged support for a deployment-based evaluation, since there will also be other considerations such as token consumption, API pricing, infrastructure cost, etc. Furthermore, the measured latency may vary because of some external factors, such as

network conditions, load, API processing, and infrastructure of the service provider, which might influence the reproducibility of the experiment results in different conditions. Thus, the latency findings are considered as the observed operational measurements in a certain experimental setting rather than intrinsic performance properties or general deployment costs of the models. The deployment conclusions have been moderated accordingly, and it is recognized that the latency and tool call numbers only provide partial insight into operational trade-offs. In the future, it would be important to include data on token consumption and monetary cost based on provider usage metadata, if possible, as well as to reproduce latency measurements under similar conditions.

Sixth, Tool Filter was evaluated only for the OpenAI models because the implemented mechanism relied on the OpenAI function-calling interface. It was not evaluated for Claude Sonnet 4.6, so Tool Filter results should not be treated as a complete cross-model comparison. In addition, the Prompt Injection Detector used the model identifier `protectai/deberta-v3-base-prompt-injection-v2` without a pinned Hugging Face revision or commit hash. Future work should pin all external model dependencies to reproducible revisions.

Seventh, this study evaluated defenses individually rather than as layered combinations. Real deployments may combine prompt structuring, learned detection, action restrictions, access control, monitoring, and human review. The effects of such combinations cannot be inferred from the individual defense results because the mechanisms may interact in ways that change both security outcomes and legitimate task completion.

Eighth, token consumption and monetary cost could not be recovered from the available traces, so the latency and tool-call counts reported in Table 12 are partial proxies for operational cost rather than complete efficiency measures.

Ninth, even though the empirical findings hinge on a certain configuration, the evaluation provides a generalizable decision-making framework in analyzing the efficacy of a defense. This research does not make an argument in favor of any of the considered defenses being the absolute best in all models or situations of application. On the contrary, this study suggests that a multidimensional evaluation of security and utility must be considered to decide on a deployment. In detail, it is necessary to consider attack success outcome, benign utility, utility while under attack, availability/restriction of actions, operational effects, effects of attack success and residual risk tolerance in the case of a deployment. This point is important since a defense that reduces the value of the ASR might, at the same time, limit the legitimate actions or decrease benign utility, while a defense that retains utility might have residual risk of the attack. The practical significance of this research, therefore, lies not in determining the absolute rankings of the defenses, but in establishing the criterion of appropriateness of a certain defense for a certain deployment requirement.

Finally, few replications limit the validity of the statistical analysis. Two independent replications were run for each experiment, which is not enough to draw reliable conclusions on the stochastic variation of LLM behavior. Thus, ASR differences are treated as descriptive or directional conclusions but not as proof of difference in defense effectiveness. No comparison pair was found statistically significant after Holm's adjustment, and the relatively low number of attack success cases decreases statistical power even more. For future studies, it would be reasonable to conduct a higher number of independent replications and use a higher number of attack samples and benchmarks to estimate the defense effectiveness reliably.

8. Conclusions

This study evaluated indirect prompt injection defenses for tool-using LLM agents using the AgentDojo banking benchmark. It reported attack success outcomes together

with benign utility, utility under attack, operational measures, goal completability evidence, and run-to-run variation. The findings should be interpreted as evidence for the specific models, defenses, action sets, task distribution, benchmark version, and replication design evaluated in this study, rather than as general measures of model robustness or defense effectiveness.

The raw undefended attack success counts were 0/288 for GPT-5.4, 11/288 for GPT-5.4-mini, and 1/288 for Claude Sonnet 4.6. These differences should not be interpreted as a direct ranking of intrinsic resistance to indirect prompt injection because the benchmark goals were not equally reachable across the evaluated models. The goal completability canary results and the feasibility-conditioned estimates show that the raw ASR reflects both the response to injected instructions and whether the underlying attack objective was completed in the evaluated setting.

The defense results showed security–utility trade-offs rather than a universally dominant configuration. For GPT-5.4-mini, the Prompt Injection Detector and Tool Filter were associated with lower observed attack success than the undefended configuration, but none of the four single-run paired comparisons reached statistical significance after Holm correction; only Tool Filter had an unadjusted p -value below 0.05. Both configurations were also associated with lower observed benign utility. Tool Filter further changed the action set available to the agent, so its observed ASR outcomes must be interpreted alongside its restrictions on tool use and its effects on legitimate task completion.

The prompt-based defenses retained higher observed benign utility in several configurations, but the available results did not establish a consistent security advantage. More generally, a lower observed ASR has limited practical meaning if it is accompanied by substantial loss of legitimate task completion or by a substantial restriction of the actions available to the agent. Practically speaking, defense selection should be regarded as a deployment decision, not a simple ranking decision. Potential defenses should be assessed in parallel based on attack success outcomes, benign utility, utility under attack, action availability and constraints, operational effects, consequences of a successful attack, and tolerable residual risk.

When high-consequence external actions or broad tool access is required in a deployment, a defense which limits or validates agent actions may be considered when the consequence of a successful attack exceeds the cost of reducing legitimate task completion. However, before considering any limitations on agent actions, the necessity of the limited actions to complete a legitimate task should be checked. If reliable legitimate-task completion is necessary in a deployment, potential defenses that result in a significant reduction in benign utility should be approached with caution. Content-level detection approaches are likely to add security benefits, yet the security gain achieved through these defenses should also be compared with their negative impacts on legitimate task completion. In case operational continuity and utility are the major concerns and tolerable residual attack risk is present, the mechanism that allows retaining more legitimate functionality might be more applicable. Hence, an appropriate defense is not defined only by the ASR but also depends on the security and functionality needs of the target deployment.

These conclusions present a generalizable framework for decision making while keeping the generalization of empirical results within reasonable bounds. First, this paper does not claim that any of the defenses presented here is universally better in terms of ASR, benign utility, utility under attack, action availability, operational effects, attack consequences, and residual-risk tolerance. This research proves the usefulness of multidimensional evaluation of the security and functionality measures for selecting an appropriate defense. The ASR, benign utility, utility under attack, action availability, operational effects, attack consequences, and residual-risk tolerance can be used as complementary evidence for

assessing the suitability of a defense for a certain deployment. The numbers obtained during experiments should be recalculated for different models, tasks, tools, attack strategies, and providers.

The repeated benchmark runs showed that benign utility was generally more stable than individual low-frequency attack outcomes. Accordingly, defense rankings based on a single-run attack success estimate should be treated cautiously, particularly when event counts are small. Future work should evaluate additional agent environments, task suites, attack families, model versions, and layered defense combinations. It should also report goal feasibility, action restrictions, benign utility, utility under attack, operational measures, uncertainty, and replication results explicitly.

Author Contributions: Conceptualization, A.K.; methodology, A.K.; software, A.K.; validation, A.K.; formal analysis, A.K.; investigation, A.K. and K.A.; data curation, A.K.; writing—original draft preparation, A.K.; literature review, K.A.; writing—review and editing, K.A. and A.M.; visualization and journal format preparation, A.M. All authors have read and agreed to the published version of the manuscript.

Funding: This research received no external funding.

Data Availability Statement: The code, frozen result files, per-defense traces, headline figure, and table-generation scripts that support the findings of this study are openly available on Zenodo at <https://doi.org/10.5281/zenodo.20731176> (accessed on 27 August 2026).

Acknowledgments: The authors thank Liwa University, Abu Dhabi, and the General Education Department for institutional support and the computing resources used in this study.

Conflicts of Interest: The authors declare no conflicts of interest.

References

1. Greshake, K.; Abdelnabi, S.; Mishra, S.; Endres, C.; Holz, T.; Fritz, M. Not What You've Signed Up For: Compromising Real-World LLM-Integrated Applications with Indirect Prompt Injection. In *Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security (AISec)*; ACM: New York, NY, USA, 2023; pp. 79–90. [\[CrossRef\]](#)
2. Yi, J.; Xie, Y.; Zhu, B.; Kiciman, E.; Sun, G.; Xie, X.; Wu, F. Benchmarking and Defending against Indirect Prompt Injection Attacks on Large Language Models. In *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining*; ACM: New York, NY, USA, 2025; pp. 1809–1820. [\[CrossRef\]](#)
3. Reddy, P. Weaponizing Words: Direct & Indirect Prompt Injection Attacks on LLM. In *Proceedings of the 26th ACM Annual Conference on Cybersecurity & Information Technology Education*; ACM: New York, NY, USA, 2025; pp. 292–293. [\[CrossRef\]](#)
4. Joseph, J.K.; Daniel, E.; Kathiresan, V.; Manimegalai, M.A.P. Prompt Injection in Large Language Model Exploitation: A Security Perspective. In *Proceedings of the 2025 International Conference on Electronics, Computing, Communication and Control Technology (ICECCC)*; IEEE: Piscataway, NJ, USA, 2025; pp. 1–8. [\[CrossRef\]](#)
5. Debenedetti, E.; Zhang, J.; Balunović, M.; Beurer-Kellner, L.; Fischer, M.; Tramèr, F. AgentDojo: A Dynamic Environment to Evaluate Prompt Injection Attacks and Defenses for LLM Agents. In *Advances in Neural Information Processing Systems 37 (NeurIPS 2024)*; Datasets and Benchmarks Track; Curran Associates, Inc.: Red Hook, NY, USA, 2024; pp. 82895–82920. [\[CrossRef\]](#)
6. Zhan, Q.; Liang, Z.; Ying, Z.; Kang, D. InjecAgent: Benchmarking Indirect Prompt Injections in Tool-Integrated Large Language Model Agents. In *Findings of the Association for Computational Linguistics: ACL 2024*; Association for Computational Linguistics: Stroudsburg, PA, USA, 2024; pp. 10471–10506. [\[CrossRef\]](#)
7. Ning, L.; Wang, S.; Fan, W.; Li, Q.; Xu, X.; Chen, H.; Huang, F. CheatAgent: Attacking LLM-Empowered Recommender Systems via LLM Agent. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*; ACM: New York, NY, USA, 2024; pp. 2284–2295. [\[CrossRef\]](#)
8. Zhang, B.; Xin, H.; Fang, M.; Liu, Z.; Yi, B.; Li, T.; Liu, Z. Traceback of Poisoning Attacks to Retrieval-Augmented Generation. In *Proceedings of the ACM on Web Conference 2025 (WWW '25)*; ACM: New York, NY, USA, 2025; pp. 2085–2097. [\[CrossRef\]](#)
9. Cheng, Z.; Sun, J.; Gao, A.; Quan, Y.; Liu, Z.; Hu, X.; Fang, M. Secure Retrieval-Augmented Generation Against Poisoning Attacks. In *Proceedings of the 2025 IEEE International Conference on Big Data (BigData)*; IEEE: Piscataway, NJ, USA, 2025; pp. 1799–1806. [\[CrossRef\]](#)
10. Nazary, F.; Deldjoo, Y.; Di Noia, T. Poison-RAG: Adversarial Data Poisoning Attacks on Retrieval-Augmented Generation in Recommender Systems. In *Lecture Notes in Computer Science*; Springer: Cham, Switzerland, 2025; pp. 239–251. [\[CrossRef\]](#)

11. Ward, C.M.; Harguess, J. Adversarial Threat Vectors and Risk Mitigation for Retrieval-Augmented Generation Systems. In *Proceedings of SPIE: Assurance and Security for AI-Enabled Systems*; SPIE: Bellingham, WA, USA, 2025; p. 11. [\[CrossRef\]](#)
12. Lee, R.W.; Jun, T.J.; Lee, J.; Cho, S.I.; Park, H.J.; Suh, J. Vulnerability of Large Language Models to Prompt Injection When Providing Medical Advice. *JAMA Netw. Open* **2025**, *8*, e2549963. [\[CrossRef\]](#) [\[PubMed\]](#)
13. Pasquini, D.; Strohmeier, M.; Troncoso, C. Neural Exec: Learning (and Learning from) Execution Triggers for Prompt Injection Attacks. In *Proceedings of the 2024 Workshop on Artificial Intelligence and Security (AISec '24)*; ACM: New York, NY, USA, 2024; pp. 89–100. [\[CrossRef\]](#)
14. Shao, Z.; Liu, H.; Mu, J.; Gong, N.Z. Enhancing Prompt Injection Attacks to LLMs via Poisoning Alignment. In *Proceedings of the 18th ACM Workshop on Artificial Intelligence and Security (AISec '25)*; ACM: New York, NY, USA, 2025; pp. 13–27. [\[CrossRef\]](#)
15. Shi, J.; Yuan, Z.; Liu, Y.; Huang, Y.; Zhou, P.; Sun, L.; Gong, N.Z. Optimization-Based Prompt Injection Attack to LLM-as-a-Judge. In *Proceedings of the 2024 ACM SIGSAC Conference on Computer and Communications Security (CCS '24)*; ACM: New York, NY, USA, 2024; pp. 660–674. [\[CrossRef\]](#)
16. Lee, S.; Kim, J.; Pak, W. Mind Mapping Prompt Injection: Visual Prompt Injection Attacks in Modern Large Language Models. *Electronics* **2025**, *14*, 1907. [\[CrossRef\]](#)
17. Kwon, H.; Pak, W. Text-Based Prompt Injection Attack Using Mathematical Functions in Modern Large Language Models. *Electronics* **2024**, *13*, 5008. [\[CrossRef\]](#)
18. Taveekitworachai, P.; Abdullah, F.; Gursesli, M.C.; Dewantoro, M.F.; Chen, S.; Lanata, A.; Guazzini, A.; Thawonmas, R. Breaking Bad: Unraveling Influences and Risks of User Inputs to ChatGPT for Game Story Generation. In *Lecture Notes in Computer Science*; Springer: Cham, Switzerland, 2023; pp. 285–296. [\[CrossRef\]](#)
19. Zhu, X.; Wang, Y.; Gao, H.; Xu, W.; Wang, C.; Liu, Z.; Wang, K.; Jin, M.; Pang, L.; Weng, Q.; et al. Recommender Systems Meet Large Language Model Agents: A Survey. *Found. Trends Priv. Secur.* **2025**, *7*, 247–396. [\[CrossRef\]](#)
20. Hines, K.; Lopez, G.; Hall, M.; Zarfati, F.; Zunger, Y.; Kiciman, E. Defending Against Indirect Prompt Injection Attacks with Spotlighting. *arXiv* **2024**, arXiv:2403.14720. [\[CrossRef\]](#)
21. Jacob, D.; Alzahrani, H.; Hu, Z.; Alomair, B.; Wagner, D. PromptShield: Deployable Detection for Prompt Injection Attacks. In *Proceedings of the Fifteenth ACM Conference on Data and Application Security and Privacy (CODASPY '25)*; ACM: New York, NY, USA, 2025; pp. 341–352. [\[CrossRef\]](#)
22. Omri, S.; Abdelkader, M.; Hamdi, M. MalPID: Malicious Prompt Injection Detection Dataset for Large Language Model Based Applications. In *Proceedings of the 2024 IEEE Eleventh International Conference on Communications and Networking (ComNet)*; IEEE: Piscataway, NJ, USA, 2024; pp. 1–5. [\[CrossRef\]](#)
23. Yung, C.; Dolatabadi, H.M.; Erfani, S.; Leckie, C. Round Trip Translation Defence Against Large Language Model Jailbreaking Attacks. In *Lecture Notes in Computer Science*; Springer: Singapore, 2025; pp. 286–297. [\[CrossRef\]](#)
24. Ouyang, F.; Zhang, D.; Xie, C.; Wang, H.; Xiang, T. LLMBD: Backdoor Defense via Large Language Model Paraphrasing and Data Voting in NLP. *Knowl.-Based Syst.* **2025**, *324*, 113737. [\[CrossRef\]](#)
25. Yu, Q.; Cheng, X.; Liu, C. Defense Against Indirect Prompt Injection via Tool Result Parsing. *arXiv* **2026**, arXiv:2601.04795. [\[CrossRef\]](#)
26. Wang, C.; Zhang, F.; Zhang, J.; Zhang, Z.; Wang, Y.; Huang, L.; Gao, J.; Chen, Z.; Lim, W.Y.B. ICON: Indirect Prompt Injection Defense for Agents Based on Inference-Time Correction. *arXiv* **2026**, arXiv:2602.20708. [\[CrossRef\]](#)
27. He, Y.; Zhu, H.; Li, Y.; Shao, S.; Yao, H.; Liu, Z.; Qin, Z. AttriGuard: Defeating Indirect Prompt Injection in LLM Agents via Causal Attribution of Tool Invocations. *arXiv* **2026**, arXiv:2603.10749. [\[CrossRef\]](#)
28. Wang, C.; Zhang, J.; Zhang, Z.; Wang, Z.; Wang, Y.; Gao, J.; Wei, T.; Chen, Z.; Lim, W.Y.B. AdapTools: Adaptive Tool-Based Indirect Prompt Injection Attacks on Agentic LLMs. *arXiv* **2026**, arXiv:2602.20720. [\[CrossRef\]](#)
29. Syros, G.; Rose, E.; Grinstead, B.; Kerschbaumer, C.; Robertson, W.; Nita-Rotaru, C.; Oprea, A. MUZZLE: Adaptive Agentic Red-Teaming of Web Agents Against Indirect Prompt Injection Attacks. *arXiv* **2026**, arXiv:2602.09222. [\[CrossRef\]](#)
30. Cao, D.; Yu, B. Survey of Emerging Trends in LLM Agent Benchmarking. In *Proceedings of the 2025 2nd Symposium on Big Data, Neural Networks, and Deep Learning*; ACM: New York, NY, USA, 2025; pp. 31–35. [\[CrossRef\]](#)
31. Ren, Z.; Li, J.; Zhang, M.; Wang, D.; Fan, X.; Shangguan, L. Toward Sensor-In-the-Loop LLM Agent: Benchmarks and Implications. In *Proceedings of the 23rd ACM Conference on Embedded Networked Sensor Systems (SenSys '25)*; ACM: New York, NY, USA, 2025; pp. 254–267. [\[CrossRef\]](#)
32. Singh, A.; Kumar, S.; Ehtesham, A.; Khoei, T.T.; Bhati, D. Large Language Model-Driven Immersive Agent. In *Proceedings of the 2024 IEEE World AI IoT Congress (AIoT)*; IEEE: Piscataway, NJ, USA, 2024; pp. 619–624. [\[CrossRef\]](#)
33. Ren, Y.; Wang, J.; Zhao, Z.; Wen, H.; Li, H.; Zhu, H. Automated Tactics Planning for Cyber Attack and Defense Based on Large Language Model Agents. *Neural Netw.* **2025**, *191*, 107842. [\[CrossRef\]](#) [\[PubMed\]](#)
34. Qi, X.; Huang, K.; Panda, A.; Henderson, P.; Wang, M.; Mittal, P. Visual Adversarial Examples Jailbreak Aligned Large Language Models. *Proc. AAAI Conf. Artif. Intell.* **2024**, *38*, 21527–21536. [\[CrossRef\]](#)

35. Hou, W.; Hu, N.; Hu, Y.; Luo, W. Large Language Model Jailbreak Based on Stylistic Rewriting. In *Proceedings of the 2025 IEEE 10th International Conference on Data Science in Cyberspace (DSC)*; IEEE: Piscataway, NJ, USA, 2025; pp. 480–486. [\[CrossRef\]](#)
36. Yang, Z.; Fan, J.; Yan, A.; Gao, E.; Lin, X.; Li, T.; Mo, K.; Dong, C. Distraction Is All You Need for Multimodal Large Language Model Jailbreaking. In *Proceedings of the 2025 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*; IEEE: Piscataway, NJ, USA, 2025; pp. 9467–9476. [\[CrossRef\]](#)
37. Dong, Y.; Mu, R.; Zhang, Y.; Sun, S.; Zhang, T.; Wu, C.; Jin, G.; Qi, Y.; Hu, J.; Meng, J.; et al. Safeguarding Large Language Models: A Survey. *Artif. Intell. Rev.* **2025**, *58*, 12. [\[CrossRef\]](#) [\[PubMed\]](#)
38. Mathew, E.S. Enhancing Security in Large Language Models: A Comprehensive Review of Prompt Injection Attacks and Defenses. *J. Artif. Intell.* **2025**, *7*, 347–363. [\[CrossRef\]](#)
39. Wang, Q. The Comprehensive Review on Prompt Injection Attacks and Defense Mechanisms in Large Language Models. *Sci. Technol. Eng. Chem. Environ. Prot.* **2025**, *1*, 3. [\[CrossRef\]](#)
40. Chen, B.; Zhang, Z.; Langrené, N.; Zhu, S. Unleashing the Potential of Prompt Engineering for Large Language Models. *Patterns* **2025**, *6*, 101260. [\[CrossRef\]](#) [\[PubMed\]](#)
41. Ghaffar Nia, N.; Amiri, A.; Luo, Y.; Kline, A. Ethical Perspectives on Deployment of Large Language Model Agents in Biomedicine: A Survey. *AI Ethics* **2026**, *6*, 32. [\[CrossRef\]](#)
42. Hu, Y.; Zou, F.; Han, J.; Sun, X.; Wang, Y. LLM-TIKG: Threat Intelligence Knowledge Graph Construction Utilizing Large Language Model. *Comput. Secur.* **2024**, *145*, 103999. [\[CrossRef\]](#)
43. Stein, S.; Pilgermann, M.; Weber, S.; Sedlmayr, M. Leveraging MDS2 and SBOM Data for LLM-Assisted Vulnerability Analysis of Medical Devices. *Comput. Struct. Biotechnol. J.* **2025**, *28*, 267–280. [\[CrossRef\]](#) [\[PubMed\]](#)
44. Liu, X.; Lin, J.; Dong, W.; Tang, Z.; Wang, Y. Large Language Model-Assisted Security Testing for Embedded Systems. In *Proceedings of the 2025 International Conference on Signal Processing, Computer Networks and Communications (SPCNC)*; IEEE: Piscataway, NJ, USA, 2025; pp. 630–636. [\[CrossRef\]](#)
45. Li, Y.; Ding, Z.; Yan, Z.; Li, Z.; Shao, H. Insider Threat Detection Based on Knowledge Graph and Large Language Model. In *Proceedings of the 2024 7th International Conference on Data Science and Information Technology (DSIT)*; IEEE: Piscataway, NJ, USA, 2024; pp. 1–4. [\[CrossRef\]](#)
46. Li, K.; Liu, H.; Zhang, L.; Chen, Y. Automatic Inspection of Static Application Security Testing (SAST) Reports via Large Language Model Reasoning. In *Communications in Computer and Information Science*; Springer: Singapore, 2025; pp. 128–142. [\[CrossRef\]](#) [\[PubMed\]](#)
47. Kalaiselvi, B.; Anbarasan, S.; Pargau, R.A.; Raja, G. ZeroByX: A Cyber Security Specialized Large Language Model (LLM). In *Proceedings of the 2025 IEEE 2nd International Conference on Information Technology, Electronics and Intelligent Communication Systems (ICITEICS)*; IEEE: Piscataway, NJ, USA, 2025; pp. 1–6. [\[CrossRef\]](#)
48. Wilson, E.B. Probable Inference, the Law of Succession, and Statistical Inference. *J. Am. Stat. Assoc.* **1927**, *22*, 209–212. [\[CrossRef\]](#)
49. McNemar, Q. Note on the Sampling Error of the Difference Between Correlated Proportions or Percentages. *Psychometrika* **1947**, *12*, 153–157. [\[CrossRef\]](#) [\[PubMed\]](#)
50. Holm, S. A Simple Sequentially Rejective Multiple Test Procedure. *Scand. J. Stat.* **1979**, *6*, 65–70.
51. Zhan, Q.; Fang, R.; Panchal, H.S.; Kang, D. Adaptive Attacks Break Defenses Against Indirect Prompt Injection Attacks on LLM Agents. In *Findings of the Association for Computational Linguistics: NAACL 2025*; Association for Computational Linguistics: Stroudsburg, PA, USA, 2025; pp. 7116–7132. [\[CrossRef\]](#)

Disclaimer/Publisher’s Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.